Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
1. 2. 3.	00977	ANTHRO RETAIL DBL VERTICAL FOLD & N O LENGTH FOLD	ANTHRO RETAIL DBL VERTICAL FOLD & N O LENGTH FOLD	00207	MGRS. ONLY	00004	PACKING	
1, 2, 3, 1 r	00978	ANTHRO RETAIL NO FOLD	ANTHRO RETAIL NO FOLD ENCASE GARM ENT IN POLYBAG. PO LYBAG LENGTH MUS T = MINIMUM 4" LON GER THAN FINISHED GARMENT LENGTH. ROLL UP BAG OPENI NG TO FINISH 1" BEL OW GARMENT HEM A ND TAPE CLOSED. D O NOT FOLD.	00207	MGRS. ONLY	00004	PACKING	
	01306	ANTHRO SINGLE FO LD PACK	ANTHRO SINGLE FO LD PACK POLYBAGS SHOULD BE ORDERE D ACCORDING TO SI ZE. GARMENT MUST FIT IN STANDARD BO X SIZE. STEP #1: FOL D SLEEVES IN TOWA RDS BACK BODY IF N ECESSARY DO NOT F OLD THROUGH SHO ULDERS UNLESS EX CEEDING 16" WIDTH STEP #2 FOLD GARM ENT IN HALF LENGT HWISE.	00078	WOMEN'S SHIRTS/BL OUSES	00004	PACKING	
	01307	ANTHRO SINGLE FOL D PACK-EMBELLISHE D STYLES.	ANTHRO SINGLE FOL D PACK-EMBELLISHE D STYLES. POLYBAG S SHOULD BE ORDE RED ACCORDING TO SIZE. GARMENT MUS T FIT IN STANDARD B OX SIZE. STEP #1: PL ACE TISSUE ON FRO NT & BACK BODY. ST EP #2: FOLD SLEEVE S IN TOWARDS BACK BODY IF NECESSARY DO NOT FOLD THRO UGH SHOULDERS UN LESS EXCEEDING 16 "WIDTH STEP #3: FO	00078	WOMEN'S SHIRTS/BL OUSES	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			LD GARMENT IN HAL F LENGTHWISE.					
	00815	ANTHRO WHOLESAL E BLOUSE SINGLE F OLD	ANTHRO WHOLESAL E BLOUSE SINGLE F OLD MUST SHIP GAR MENT ON SPECIFIED LEIFSDOTTIR HANG ER & FOLD TO FIT W ITHIN SPECIFIED BO X SIZE AS SHOWN IN PHOTO. ENCASE GA RMENT IN POLYBAG. POLYBAG LENGTH M UST = MINIMUM 4" LO NGER THAN FINISHE D GARMENT LENGTH . ROLL UP BAG OPEN ING TO FINISH 1" BEL OW GARMENT HEM A ND TAPE CLOSED. M AXIMUM SINGLE LEN GTH FOLD AS NEEDE D TO FIT IN SPECIFIE D CONTAINER.	00078	WOMEN'S SHIRTS/BL OUSES	00004	PACKING	
Sealer Webside North Auto- Seage Materials and Auto- Sealer Auto-Auto-Auto-Auto-Auto-Auto-Auto-Auto-	00819	ANTHRO WHOLESAL E COAT SINGLE FOL D ON HANGER	ANTHRO WHOLESAL E COAT SINGLE FOLD ON HANGER MUST SHIP GARMENT ON S PECIFIED LEIFSDOT TIR HANGER & FOLD TO FIT WITHIN SPEC IFIED BOX SIZE AS SHOWN IN PHOTO. *P ACKED POLY BAG DIMENSIONS MUST NOT EXCEED 23L X 16 W ENCASE GARMEN TIN POLYBAG. POLYBAG LENGTH MUST = MINIMUM 4" LONGER THAN FINISHED GAR MENT LENGTH. ROLL UP BAG OPENING TO FINISH 1" BELOW GARMENT HEM AND TAPE CLOSED. MAXIMUM SINGLE LENGTH FOLD AS NEEDED TO FIT IN SPECIFIED CONTAINER.	00073	JACKETS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem	Construction Elem ent Desc	Status
Antion of thousand a long Cast Packargo. The Company of the Cast Section of the Cast S	00820	ANTHRO WHOLESAL E COAT TRIPPLE ZIG ZAG FOLD	ANTHRO WHOLESAL E COAT TRIPPLE ZIG ZAG FOLD MUST SHI P GARMENT ON SPE CIFIED LEIFSDOTTIR HANGER & FOLD TO FIT WITHIN SPECIFIE D BOX SIZE AS SHO WN IN PHOTO. *PAC KED POLY BAG DIME NSIONS MUST NOT E XCEED 23L X 16W EN CASE GARMENT IN P OLYBAG. POLYBAG L ENGTH MUST = MINI MUM 4" LONGER THA N FINISHED GARMEN T LENGTH. ROLL UP BAG OPENING TO FI NISH 1" BELOW GAR MENT HEM AND TAP E CLOSED. MAXIMUM SINGLE LENGTH FO LD AS NEEDED TO FI T IN SPECIFIED CON TAINER.	00073	JACKETS	00004	PACKING	
	00979	ANTHRO WHOLESAL E DBL VERTICAL & SI NGLE LENGTH FOLD	ANTHRO WHOLESAL E DBL VERTICAL & SI NGLE LENGTH FOLD SHIP ON SPECIFIED HANGER ACCORDIN G TO LEIFSDOTTIR S HIPPING GUIDE. ENC ASE GARMENT IN PO LYBAG. POLYBAG LE NGTH MUST = MINIM UM 4" LONGER THAN FINISHED GARMENT LENGTH. ROLL UP B AG OPENING TO FIN ISH 1" BELOW GARM ENT HEM AND TAPE CLOSED.	00207	MGRS. ONLY	00004	PACKING	
	00821	ANTHRO WHOLESAL E DOUBLE FOLDED P ANT ON HANGER	ANTHRO WHOLESAL E DOUBLE FOLDED P ANT ON HANGER	00072	PANT/SHORTS	00004	PACKING	
Motion Principal Set Facility and in The Conference of Conference of Set	00980	ANTHRO WHOLESAL E NO FOLD ON HAN GER	ANTHRO WHOLESAL E NO FOLD ON HANG ER SKIRT LENGTH M UST NOT EXCEED 18 "SHIP ON SPECIFIED HANGER ACCORDIN G TO LEIFSDOTTIR S HIPPING GUIDE. ENC ASE GARMENT IN PO LYBAG. POLYBAG LE	00207	MGRS. ONLY	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			NGTH MUST = MINIM UM 4" LONGER THAN FINISHED GARMENT LENGTH. ROLL UP B AG OPENING TO FIN ISH 1" BELOW GARM ENT HEM AND TAPE CLOSED.					
Agency body and short haden being the state of the state	00817	ANTHRO WHOLESAL E SHORT JACKET SIN GLE FOLD	ANTHRO WHOLESAL E SHORT JACKET SI NGLE FOLD MUST S HIP GARMENT ON SP ECIFIED LEIFSDOTTI R HANGER & FOLD T O FIT WITHIN SPECIFIED BOX SIZE AS SH OWN IN PHOTO. *PA CKED POLY BAG DIM ENSIONS MUST NOT EXCEED 23L X 16W E NCASE GARMENT IN POLYBAG. POLYBAG LENGTH MUST = MIN IMUM 4" LONGER TH AN FINISHED GARME NT LENGTH. ROLL U P BAG OPENING TO FINISH 1" BELOW GAR MENT HEM AND TAP E CLOSED. MAXIMUM SINGLE LENGTH FO LD AS NEEDED TO FI T IN SPECIFIED CON TAINER.	00073	JACKETS	00004	PACKING	
	00976	ANTHRO WHOLESAL E SINGLE LENGTH & NO VERTICAL FOLD	ANTHRO WHOLESAL E SINGLE LENGTH & NO VERTICAL FOLD	00207	MGRS. ONLY	00004	PACKING	
	00818	ANTHRO WHOLESAL E TRIPPLE ZIG ZAG F OLD ON HANGER	ANTHRO WHOLESAL E TRIPPLE ZIG ZAG F OLD ON HANGER MU ST SHIP GARMENT O N SPECIFIED LEIFSD OTTIR HANGER & FO LD TO FIT WITHIN SP ECIFIED BOX SIZE AS SHOWN IN PHOTO. E NCASE GARMENT IN POLYBAG. POLYBAG LENGTH MUST = MIN IMUM 4" LONGER TH AN FINISHED GARME NT LENGTH. ROLL U P BAG OPENING TO FINISH 1" BELOW GAR MENT HEM AND TAP E CLOSED. MAXIMUM	00075	SHIRTS/DRESSES/JU MPERS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			SINGLE LENGTH FOL D AS NEEDED TO FIT IN SPECIFIED CONTA INER. *PACKED POLY BAG DIMENSIONS M UST NOT EXCEED 23 L X 16W					
	00981	ANTHROPOLOGIE W HOLESALE	ANTHROPOLOGIE W HOLESALE MUST SH IP GARMENT ON SPE CIFIED LEIFSDOTTIR HANGER & FOLD TO FIT WITHIN SPECIFIE D BOX SIZE AS SHO WN IN PHOTO. ENCA SE GARMENT IN POL YBAG. POLYBAG LEN GTH MUST = MINIMU M 4" LONGER THAN F INISHED GARMENT L ENGTH. ROLL UP BA G OPENING TO FINIS H 1" BELOW GARME NT HEM AND TAPE C LOSED. MAXIMUM SI NGLE LENGTH FOLD AS NEEDED TO FIT I N SPECIFIED CONTA INER.	00207	MGRS. ONLY	00004	PACKING	
1. 2. 3. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.	00975	ANTHROPOLOGIE W HOLESALE DOUBLE VERTICAL FOLD	ANTHROPOLOGIE W HOLESALE DOUBLE VERTICAL FOLD SHIP ON SPECIFIED HANG ER ACCORDING TO L EIFSDOTTIR SHIPPIN G GUIDE. ENCASE G ARMENT IN POLYBA G. POLYBAG LENGTH MUST = MINIMUM 4" L ONGER THAN FINISH ED GARMENT LENGT H. ROLL UP BAG OPE NING TO FINISH 1" B ELOW GARMENT HE M AND TAPE CLOSED . MAXIMUM 2 VERTIC AL LENGTH FOLD AS NEEDED TO FIT IN SP ECIFIED CONTAINER.	00207	MGRS. ONLY	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
1. 2. 3. 1. r.	00974	ANTHROPOLOGIE W HOLESALE SKIRT NO LENGTH FOLD	ANTHROPOLOGIE W HOLESALE SKIRT NO LENGTH FOLD SHIP ON SPECIFIED HANG ER ACCORDING TO L EIFSDOTTIR SHIPPIN G GUIDE. ENCASE G ARMENT IN POLYBA G. POLYBAG LENGTH MUST = MINIMUM 4" L ONGER THAN FINISH ED GARMENT LENGT H. ROLL UP BAG OPE NING TO FINISH 1" B ELOW GARMENT HE M AND TAPE CLOSED . DO NOT FOLD.	00207	MGRS. ONLY	00004	PACKING	
	01355	BRALETTE	BRALETTE FINISHED DIMENSIONS AFTER FOLDING/ROLLING: D EPENDS ON THE LEN GTH OF THE GARME NT. POLYBAG SIZE: D O NOT ALLOW MORE THAN 1" OF SPACE B ETWEEN EDGE OF G ARMENT AND POLYB AG. NOTES TO REME MBER: "DO NOT USE PINS, CLIPS, STIFFE NERS OR CARDBOAR D WITHOUT PRIOR A PPROVAL. *TISSUE M AY BE USED ON LIGH TWEIGHT FABRICS (I .E. SILKS,RAYON, PO LYESTER ECT.) FOLD ING/ROLLING PREPA RATIONS: "PLACE GA RMENT FACE UP *AL L CLOSURES MUST B UTTON, ZIP, SNAP EC T. FOLDING/ROLLING INSTRUCTIONS: 1. F OLD STRAPS DOWN. 2. FOLD GARMENT IN CORRECT SIZE POLYB AG AND SEAL THE P OLYBAG WITH CLEA R TAPE OR HEAT SE AL. (IF THE HEAT SE AL. (IF THE HEAT SE AL ING METHOD IS USE D ALL POLYBAGS MU ST HAVE THREE HAL F MOO OR BUTTERFI	00176	BRAS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			Y VENT HOLES 1/4" D IAMETER AND EVENL Y SPACED.)					
1. 3. 3	01733	CAMI FLAT PACK WIT H FOLDED POLY BAG	CAMI FLAT PACK WIT H FOLDED POLY BAG PLACE GARMENT IN POLYBAG FLAT. POL YBAG SHOULD BE CL OSE IN SIZE TO GAR MENT. FOLD POLY B AG IN HALF AND TAP E CLOSED.	00078	WOMEN'S SHIRTS/BL OUSES	00004	PACKING	
	01655	CF BUTTONS OPEN	CF BUTTONS OPEN S HIP WITH COLLAR ST AND AND 1ST PLACK ET BUTTON OPEN.	00225	BUTTONS	00004	PACKING	
	01620	CF BUTTONS/UK	CF BUTTONS/UK SHI P WITH ALL BUTTON S CLOSED.	00225	BUTTONS	00004	PACKING	
	00687	COAT - LONG SLEEV E TRI FOLD	COAT - LONG SLEEV E TRI FOLD PACKED POLY BAG DIMENSIO NS MUST NOT EXCE ED 23L X 16W ANTHR OPOLOGIE: NO RES TRICTIONS ON POLY BAGS, FOLLOW PRO PER FOLDING AND O RDER POLYBAG ACC ORDINGLY POLYBAG S SHOULD BE ORDE RED ACCORDING TO FOLDED GARMENT U TILIZING DIMENSION S OF STANDARD CA RTON, NO EXCESS R OOM FOR GARMENT SHIFTING. DO NOT A LLOW MORE THAN 1" OF SPACE BETWEEN EDGE OF GARMENT AND POLYBAG WITH CLEAR TAPE OR HEA T SEAL! (IF THE THE T THE TORION TO THE TILL THE TORION TO THE TO THE TORION TO THE TORION TO THE TORION TO THE TORION TO THE TO THE TORION TO THE TO THE TORION TO THE TO THE TO THE TO THE T	00073	JACKETS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			EMEMBER: *DO NOT USE PINS, CLIPS, ST IFFENERS OR CARD BOARD WITHOUT PRI OR APPROVAL. *TISS UE MAY BE USED ON LIGHTWEIGHT FABRI CS (I.E. SILKS, RAYO N, POLYESTER ETC.) FOLDING INSTRUCTI ONS: SEE PHOTO **** *EXCEPTION: - DO N OT USE POLYBAGS F OR PRE-PACKS					
STORY TO AND	01644	COAT - WAIST SEAM, SINGLE FOLD	COAT - WAIST SEAM , SINGLE FOLD USE T HIS PACKING WHEN BOTTOM DETAILS O F COAT SHOULD NOT BE FOLDED, EX: PLE ATS POLYBAGS SHO ULD BE ORDERED A CCORDING TO FOLD ED GARMENT UTILIZ ING DIMENSIONS OF STANDARD CARTON, NO EXCESS ROOM F OR GARMENT SHIFT ING. DO NOT ALLOW MORE THAN 1" OF SP ACE BETWEEN EDGE OF GARMENT AND P OLYBAG. SEAL THE P OLYBAG WITH CLEA R TAPE OR HEAT SEAL (IF THE HEAT SEAL ING METHOD IS USE D ALL POLYBAGS MU ST HAVE THREE HAL F MOON OR BUTTER FLY VENT HOLES 1/4" DIAMETER AND EV ENLY SPACED.) GAR MENT MUST FIT IN S TANDARD SIZE CART ON NOTES TO REME MBER: "DO NOT USE PINS, CLIPS, STIFFE NERS OR CARDBOAM A PROVAL. "TISSUE M AY BE USED ON LIGH TWEIGHT FABRICS (I. E. SILKS, RAYON, PO LYESTER ETC.) FOLD LING INSTRUCTIONS: SEE PHOTO ***** EXC	00073	JACKETS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			EPTION : - DO NOT U SE POLYBAGS FOR P RE-PACKS					
	00688	COAT PACKING FOR FRONT DETAILS	COAT PACKING FOR FRONT DETAILS PAC KED POLY BAG DIME NSIONS MUST NOT E XCEED 23L X 16W AN THROPOLOGIE: NO R ESTRICTIONS ON PO LYBAGS, FOLLOW PR OPER FOLDING AND ORDER POLYBAG AC CORDINGLY POLYBAG GS HOULD BE ORD ERED ACCORDING T O FOLDED GARMENT UTILIZING DIMENSION SOF STANDARD CA RTON, NO EXCESS ROOM FOR GARMENT SHIFTING. DO NOT A LLOW MORE THAN 1" OF SPACE BETWEEN EDGE OF GARMENT AND POLYBAG. SEAL THE POLYBAG WITH CLEAR TAPE OR HEAT SEAL. (IF THE HEAT SEAL.) (IF	00073	JACKETS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem	Construction Elem ent Desc	Status
Conduct will be a conducted with the conducted with the conducted will be a conducted with the conducted will be a conducted with the conducted with the conducted will be a conducted with the conducted will be a conducted with the conducted will be a conducted with the conduc	00319	CONNECTION OF CA MI & PANTY	CONNECTION OF CA MI & PANTY	00175	CAMI/PANTY SETS	00004	PACKING	
	00012	DOUBLE FOLD- PKG 04	DOUBLE FOLD- PKG0 4 FINISHED DIMENSI ONS AFTER FOLDED : APPROXIMATE FOL DED DIMENSION SHO ULD BE 10"X12" OR 1 0"X14". NOTED TO RE MEMBER: *DO NOT U SE PINS, CLIPS, STIF FENERS, AND CARD BOARD WITHOUT PR IOR APPROVAL. *THE USE OF CLIPS ON BE LTS IS ACCEPTABLE. *THE USE OF TISSUE IS ACCEPTABLE FOR LIGHTWEIGHT MATE RIALS (I.E. RAYON O R SILK) FOLDING PR EPARATIONS: *PLAC E GARMENT FACE D OWN *BUTTON, SNAP , ZIP OR BUCKLE FOL DING INSTRUCTIONS : 1. FOLD SIDES OF G ARMENT IN LENGTH WISE. 2. FOLD 1/3 BO TTOM OF SKIRT UPW ARD 3. FOLD 1/3 TOP OF SKIRT DOWNWAR D 3. PLACE THE FOL DED GARMENT INTO THE CORRECT SIZE POLYBAG AND SEAL THE POLYBAG WITH CLEAR TAPE OR HEA T SEAL. (IF THE HEA T SEAL. (IF THE HEA T SEALLING METHOD I S USED ALL POLYBA GS MUST HAVE THR EE HALF MOON OR B UTTERFLY VENT HOL ES1/4" DIAMETER AN D EVENLY SPACED.)	00071	SKIRTS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
	00278	DOUBLE LENGTH FO LD	DOUBLE LENGTH FO LD POLYBAGS SHOU LD BE ORDERED AC CORDING TO FOLDE D GARMENT UTILIZIN G DIMENSIONS OF S TANDARD CARTON, NO EXCESS ROOM F OR GARMENT SHIFT ING. DO NOT ALLOW MORE THAN 1" OF SP ACE BETWEEN EDGE OF GARMENT AND P OLYBAG WITH CLEA R TAPE OR HEAT SEA LING METHOD IS USE D ALL POLYBAGS MU ST HAVE THREE HAL F MOON OR BUTTER FLY VENT HOLES 1/4 " DIAMETER AND EV ENLY SPACED.) GAR MENT MUST FIT IN S TANDARD SIZE CART ON NOTES TO REME MBER: "DO NOT USE PINS, CLIPS, STIFFE NERS OR CARDBOAR D WITHOUT PRIOR A PPROVAL. "TISSUE M AY BE USED ON LIGH TWEIGHT FABRICS (I. E. SILKS, RAYON, PO LYESTER ETC.) FOLD ING INSTRUCTIONS: SEE PHOTO	00075	SHIRTS/DRESSES/JU MPERS	00004	PACKING	
	01625	DOUBLE LENGTH FO LD PKG001	DOUBLE LENGTH FO LD PKG001	00078	WOMEN'S SHIRTS/BL OUSES	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem	Construction Elem ent Desc	Status
	01626	DOUBLE LENGTH FO LD PKG001	DOUBLE LENGTH FO LD PKG001	00226	PACKING NOTES	00004	PACKING	
	00006	DOUBLE LENGTH FO LD PKG14	DOUBLE LENGTH FO LD PKG14 POLYBAG S SHOULD BE ORDE RED ACCORDING TO FOLDED GARMENT U TILIZING DIMENSION S OF STANDARD CA RTON, NO EXCESS R OOM FOR GARMENT SHIFTING. DO NOT A LLOW MORE THAN 1" OF SPACE BETWEEN EDGE OF GARMENT AND POLYBAG WITH CLEAR TAPE OR HEA T SEAL. (IF THE HEA T SEAL. (IF THE HEA T SEAL. (IF THE HEA T SEAL SEAL THE POLYBAG WITH CLEAR TAPE OR HEA T SEALING METHOD I S USED ALL POLYBA GS MUST HAVE THR EE HALF MOON OR B UTTERFLY VENT HOL ES 1/4" DIAMETER AN D EVENLY SPACED.) GARMENT MUST FIT I N STANDARD SIZE C ARTON NOTES TO R EMEMBER: *DO NOT USE PINS, CLIPS, ST IFFENERS OR CARD BOARD WITHOUT PR IOR APPROVAL. *TIS SUE MAY BE USED O N LIGHTWEIGHT FAB RICS (I.E. SILKS, RAY ON, POLYESTER ETC .) FOLDING INSTRUC TIONS: SEE PHOTO D O NOT FOLD THROU GH SHOULDERS UNL ESS SHOULDERS EX CEED 16".	00078	WOMEN'S SHIRTS/BL OUSES	00004	PACKING	
	01808	DOUBLE LENGTH FO LD @ CF/CB	DOUBLE LENGTH FO LD @ CF/CB FINISHE D DIMENSIONS AFTE R FOLDED: APPROXI MATE FOLDED DIME	00071	SKIRTS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			NSION SHOULD BE 1 0"X12" OR 10"X14". N OTED TO REMEMBE R: "DO NOT USE PIN S, CLIPS, STIFFENER S, AND CARDBOARD WITHOUT PRIOR APP ROVAL. "THE USE OF CLIPS ON BELTS IS A CCEPTABLE. "THE U SE OF TISSUE IS ACC EPTABLE FOR LIGHT WEIGHT MATERIALS (I.E. RAYON OR SILK) FOLDING PREPARATI ONS: "PLACE GARME NT FACE DOWN "BUT TON, SNAP, ZIP OR B UCKLE FOLDING INS TRUCTIONS: 1. PLAC E GARMENT FLAT FO LDED AT CF & CB 2. F OLD SIDES OF GARM ENT IN LENGTHWISE. 3. FOLD 1/3 BOTTOM OF SKIRT UPWARD 4. FOLD 1/3 TOP OF SKI RT DOWNWARD 5. PL ACE THE FOLDED GA RMENT INTO THE CO RRECT SIZE POLYBA G AND SEAL THE PO LYBAG WITH CLEAR LIFTHE HAAT SEALI NG METHOD IS USED ALL POLYBAGS MUS T HAVE THREE HALF MOON OR BUTTERFL Y VENT HOLES 1/4" DI AMETER AND EVENL Y SPACED.)					
	00011	DOUBLE LENGTH FO LD- PKG07	DOUBLE LENGTH FO LD- PKG07	00072	PANT/SHORTS	00004	PACKING	

Overview Locati	on Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
2.	01749	DRESS FLAT PACK W ITH FOLDED POLY B AG	DRESS FLAT PACK W ITH FOLDED POLY BA G LAY TISSUE PAPER ON FRONT OF GARM ENT. PLACE GARMEN T IN POLY BAG FLAT . BAG SHOULD BE AS CLOSE IN SIZE TO G ARMENT AS POSSIBL E. FOLD BAG IN HALF . TAPE CLOSED.	00075	SHIRTS/DRESSES/JU MPERS	00004	PACKING	
SEP FACE INCIDENCE THE TIME T	01722	DRESS IN GARMENT BAG - SINGLE FOLD	DRESS IN GARMENT BAG - SINGLE FOLD POLYBAGS SHOULD BE ORDERED ACCOR DING TO FOLDED GA RMENT UTILIZING DI MENSIONS OF STAN DARD CARTON, NO E XCESS ROOM FOR G ARMENT SHIFTING. D O NOT ALLOW MORE THAN 1" OF SPACE B ETWEEN EDGE OF G ARMENT AND POLYB AG. SEAL THE POLY BAG WITH CLEAR TA PE OR HEAT SEAL. (I F THE HEAT SEALING METHOD IS USED AL L POLYBAGS MUST H AVE THREE HALF MO ON OR BUTTERFLY V ENT HOLES 1/4" DIAM ETER AND EVENLY S PACED.) GARMENT M UST FIT IN STANDAR D SIZE CARTON NOT ES TO REMEMBER: * DO NOT USE PINS, C LIPS, STIFFENERS O R CARDBOARD WITH OUT PRIOR APPROV AL. *TISSUE MAY BE USED ON LIGHTWEIG HT FABRICS (I.E. SIL KS, RAYON, POLYES TER ETC.) FOLDING I NSTRUCTIONS: SEE PHOTO	00075	SHIRTS/DRESSES/JU MPERS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem	Construction Elem ent Desc	Status
1.	00849	DRESS ROLL PACK	DRESS ROLL PACK FI NISHED DIMENSIONS AFTER FOLDING/RO LLING: DEPENDS ON THE LENGTH OF THE GARMENT. POLYBAG SIZE: DO NOT ALLOW MORE THAN 1" OF S PACE BETWEEN EDG E OF GARMENT AND POLYBAG. NOTES TO REMEMBER: *DO NO T USE PINS, CLIPS, S TIFFENERS OR CARD BOARD WITHOUT PR IOR APPROVAL. *TIS SUE MAY BE USED O N LIGHTWEIGHT FAB RICS (I.E. SILKS,RAY ON, POLYESTER ECT .) FOLDING/ROLLING PREPARATIONS: *PL ACE GARMENT FACE DOWN *ALL CLOSUR ES MUST BUTTON, Z IP, SNAP ECT. FOLDI NG/ROLLING INSTRU CTIONS: 1. FOLD THE LEFT & RIGHT SIDE O F GARMENT OVER O N THE FOLD LINES 2 . ROLL GARMENT FR OM THE BOTTOM TO THE TOP IN A LOOSE ROLL. 3. PLACE ROLL ED GARMENT FR OM THE BOTTOM TO THE TOP IN A LOOSE ROLL. 3. PLACE ROLL ED GARMENT FR OM THE BOTTOM TO THE TOP IN A LOOSE ROLL. 3. PLACE ROLL ED GARMENT INTO C ORRECT SIZE POLYB AG AND SEAL THE P OLYBAG WITH CLEA R TAPE OR HEAT SEA LING METHOD IS USE D ALL POLYBAGS MU ST HAVE THREE HAL F MOON OR BUTTER FLY VENT HOLES 1/4 "DIAMETER AND EVE NLY SPACED.)	00075	SHIRTS/DRESSES/JU MPERS	00004	PACKING	
	01645	DRESS-FULL CIRCL E SKIRT, WAIST SEA M/SINGLE FOLD	DRESS- FULL CIRCL E SKIRT, WAIST SEA M/SINGLE FOLD PO LYBAGS SHOULD BE ORDERED ACCORDI NG TO FOLDED GAR MENT UTILIZING DIM ENSIONS OF STANDA RD CARTON, NO EXC	00075	SHIRTS/DRESSES/JU MPERS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem	Construction Elem ent Desc	Status
			ESS ROOM FOR GAR MENT SHIFTING. DO NOT ALLOW MORE T HAN 1" OF SPACE BE TWEEN EDGE OF GA RMENT AND POLYBA G. SEAL THE POLYBA G. SEAL THE POLYBA G WITH CLEAR TAPE OR HEAT SEAL. (IF T HE HEAT SEALING M ETHOD IS USED ALL POLYBAGS MUST HA VE THREE HALF MOO N OR BUTTERFLY VE NT HOLES 1/4" DIAME TER AND EVENLY SPACED.) GARMENT MU ST FIT IN STANDARD SIZE CARTON *** MAY REQUIRE CARTON OF DIFFERENT DIME NSIONS THAN STAND ARD. MUST ALERT P RODUCTION NOTES TO REMEMBER: *DO NOT USE PINS, CLIPS, STIFFENERS OR CARDBOARD WITHOUT PRIOR APPROVAL. *T ISSUE MAY BE USED ON LIGHTWEIGHT FABRICS (I.E. SILKS, RAYON, POLYESTER ET C.) FOLDING INSTRU CTIONS: SEE PHOTO					
STOP 1 AND THE RESIDENCE OF THE RESIDENC	01639	DRESS- SINGLE FOL D	DRESS- SINGLE FOL D POLYBAGS SHOUL D BE ORDERED ACC ORDING TO FOLDED GARMENT UTILIZING DIMENSIONS OF STA NDARD CARTON, NO EXCESS ROOM FOR GARMENT SHIFTING . DO NOT ALLOW MO RE THAN 1" OF SPAC E BETWEEN EDGE O F GARMENT AND PO LYBAG. SEAL THE PO LYBAG. WITH CLEAR TAPE OR HEAT SEAL . (IF THE HEAT SEAL . (IF THE HEAT SEAL ING METHOD IS USE D ALL POLYBAGS MU ST HAVE THREE HAL F MOON OR BUTTER FLY VENT HOLES 1/4	00075	SHIRTS/DRESSES/JU MPERS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			"DIAMETER AND EVENLY SPACED.) GAR MENT MUST FIT IN STANDARD SIZE CARTON NOTES TO REMEMBER: "DO NOT USE PINS, CLIPS, STIFFENERS OR CARDBOARD WITHOUT PRIOR APPROVAL. "TISSUE MAY BE USED ON LIGHTWEIGHT FABRICS (I.E. SILKS, RAYON, POLYESTER ETC.) FOLDING INSTRUCTIONS: SEE PHOTO / TAPE CLOSED					
1. 2.	00340	DRESS/CAMI ROLL P	DRESS/CAMI ROLL P ACK FINISHED DIMEN SIONS AFTER FOLDI NG/ROLLING: DEPEN DS ON THE LENGTH OF THE GARMENT. P OLYBAG SIZE: DO NO T ALLOW MORE THA N 1" OF SPACE BETW EEN EDGE OF GARM ENT AND POLYBAG. NOTES TO REMEMBE R: *DO NOT USE PINS , CLIPS, STIFFENERS OR CARDBOARD WIT HOUT PRIOR APPRO VAL. *TISSUE MAY B E USED ON LIGHTWE IGHT FABRICS (I.E. SI LKS,RAYON, POLYES TER ECT.) FOLDING/ ROLLING PREPARATI ONS: *PLACE GARME NT FACE DOWN *ALL CLOSURES MUST BU TTON, ZIP, SNAP ECT . FOLDING/ROLLING I NSTRUCTIONS: 1. FO LD THE LEFT & RIGH T SIDE OF GARMENT OVER ON THE FOLD LINES 2. ROLL GARM ENT FROM THE BOTT OM TO THE TOP IN A LOOSE ROLL. 3. PLA CE ROLLED GARMEN T INTO CORRECT SIZ E POLYBAG WIT H CLEAR TAPE OR H	00175	CAMI/PANTY SETS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			EAT SEAL. (IF THE H EAT SEALING METHO D IS USED ALL POLY BAGS MUST HAVE TH REE HALF MOO OR B UTTERFLY VENT HOL ES 1/4" DIAMETER AN D EVENLY SPACED.)					
	01378	EVENT DRESS PACK ING	EVENT DRESS PACK ING POLYBAG SIZE:1 6L X 14W NOTES TO REMEMBER: *DO NO T USE PINS, CLIPS, S TIFFENERS OR CARD BOARD WITHOUT PR IOR APPROVAL. *TIS SUE MUST BE USED FOLDING PREPARATIONS: *PLACE GARME NT FACE DOWN. *ALL CLOSURES MUST BU TTON, ZIP, SNAP ETC. FOLDING INSTRUCT IONS: SEE SKETCH P LACE THE FOLDED G ARMENT INTO THE CORRECT POLYBAG S IZE AND SEAL THE POLYBAG WITH CLEAR TAPE OR HEAT SEAL. (IF THE HEAT SEALING METHOD IS USED ALL POLYBAGS MU ST HAVE THREE HALF MOON OR BUTTER FLY VENT HOLES 1/4 *DIAMETER AND EVENLY SPACED.) USE FOR STRAPPY & STRAPLESS DRESSES	00212	WEDDING	00004	PACKING	
	01204	EVENT DRESS: DOUB LE LENGTH FOLD	EVENT DRESS: DOU BLE LENGTH FOLD P OLYBAG SIZE:NO LA RGER THAN 12" X 20 " (L X W) DO NOT ALL OW MORE THAN 1" O F SPACE BETWEEN E DGE OF GARMENT A ND POLYBAG. NOTES TO REMEMBER: *DO NOT USE PINS, CLIPS , STIFFENERS OR CA RDBOARD WITHOUT PRIOR APPROVAL. *T ISSUE MAY BE USED ON LIGHTWEIGHT FA BRICS (I.E. SILKS, RA	00212	WEDDING	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			YON, POLYESTER ET C.) FOLDING PREPAR ATIONS: *PLACE GAR MENT FACE DOWN.* ALL CLOSURES MUS T BUTTON, ZIP, SNA P ETC. FOLDING INS TRUCTIONS: 1. IF ST RARPS, FOLD DOWN AT NECKLINE 2. FOL D THE RIGHT SIDE O VER ON THE FOLD LI NE. 3. REPEAT FOR T HE LEFT SIDE. 4. FOL D IN HALF BY BRINGI NG THE BOTTOM HE M UP TO THE TOP ED GE OF DRESS. 6. PLA CE THE FOLDED GAR MENT INTO THE COR RECT POLYBAG SIZE AND SEAL THE POLY BAG WITH CLEAR TA PE OR HEAT SEAL. (IF THE HEAT SEAL.)					
	01205	EVENT DRESS: TRIPL E LENGTH FOLD	EVENT DRESS: TRIPL E LENGTH FOLD	00212	WEDDING	00004	PACKING	
	01208	EVENT SKIRT: DOUB LE FOLD- PKG04	EVENT SKIRT: DOUB LE FOLD- PKG04 FINI SHED DIMENSIONS A FTER FOLDED: APPR OXIMATE FOLDED DI MENSION SHOULD B E 10"X12" OR 10"X14" . NOTED TO REMEMB ER: *DO NOT USE PIN S, CLIPS, STIFFENER S, AND CARDBOARD WITHOUT PRIOR APP ROVAL. *THE USE OF	00212	WEDDING	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			CLIPS ON BELTS IS A CCEPTABLE. *THE U SE OF TISSUE IS ACC EPTABLE FOR LIGHT WEIGHT MATERIALS (I.E. RAYON OR SILK) FOLDING PREPARATI ONS: *PLACE GARME NT FACE DOWN *BUT TON, SNAP, ZIP OR B UCKLE FOLDING INS TRUCTIONS: 1. FOLD SIDES OF GARMENT IN LENGTHWISE. 2. FOLD 1/3 BOTTOM OF SKIRT UPWARD 3. FOLD 1/3 TOP OF SKIRT DOWNWARD 3. PLACE THE FOLDED GAR MENT INTO THE COR RECT SIZE POLYBAG AND SEAL THE POLY BAG WITH CLEAR TA PE OR HEAT SEAL. (I F THE HEAT SEALING METHOD IS USED AL L POLYBAGS MUST HAVE THREE HALF MOON OR BUTTERFLY VENT HOLES1/4" DIAM ETER AND EVENLY S PACED.)					
the agency and the	01207	EVENT SKIRT: FULL CIRCLE FOLD- PKG01	EVENT SKIRT: FULL CIRCLE FOLD- PKG01	00212	WEDDING	00004	PACKING	
1, 2, 3, 1, y	01209	EVENT SKIRT: NO F OLD	EVENT SKIRT: NO FO LD ENCASE GARMEN T IN POLYBAG. POLY BAG LENGTH MUST = MINIMUM 4" LONGER THAN FINISHED GAR MENT LENGTH. ROL L UP BAG OPENING T O FINISH 1" BELOW G ARMENT HEM AND T APE CLOSED. DO NO T FOLD.	00212	WEDDING	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem	Construction Elem ent Desc	Status
	01206	EVENT SKIRT: SINGL E FOLD PACK	EVENT SKIRT: SINGL E FOLD PACK FINISH ED DIMENSIONS AFT ER FOLDED: APPROX IMATE FOLDED DIME NSION SHOULD BE 1 0"X12" OR 10"X14". N OTED TO REMEMBE R: "DO NOT USE PIN S, CLIPS, STIFFENER S, AND CARDBOARD WITHOUT PRIOR APP ROVAL. "THE USE OF CLIPS ON BELTS IS A CCEPTABLE. "THE U SE OF TISSUE IS ACC EPTABLE FOR LIGHT WEIGHT MATERIALS (I.E. RAYON OR SILK) FOLDING PREPARAT IONS: "PLACE GARM ENT FACE DOWN "BU TTON, SNAP, ZIP OR BUCKLE FOLDING IN STRUCTIONS: 1. FOLD SIDES OF GARMEN T IN LENGTHWISE. 2. FOLD BOTTOM OF SKIRT UP TO THE TOP OF SKIRT. 3. PLACE T HE FOLDED GARMEN T INTO THE CORREC T SIZE POLYBAG AN D SEAL THE POLYBA G WITH CLEAR TAPE OR HEAT SEAL. (IF T HE HEAT SEALING M ETHOD IS USED ALL POLYBAGS MUST HA VE THREE HALF MO ON OR BUTTERFLY V ENT HOLES1/4" DIAM ETER AND EVENLY S PACED.)	00212	WEDDING	00004	PACKING	
	00235	FLAT (JEAN) FOLD W ITH VERTICAL ROLL & TIE	FLAT (JEAN) FOLD W ITH VERTICAL ROLL & TIE	00072	PANT/SHORTS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
	00083	FLAT BROOMSTICK	FLAT BROOMSTICK F INISHED DIMENSION S AFTER FOLDING: F OLDING DIMENSIONS DEPEND ON LENGTH OF GARMENT. POLY BAG SHOULD BE OR DERED ACCORDING LY TO ASSURE THAT GARMENT FITS TIGH TLY IN BAG TO HOLD PACKING TECHNIQU E. IF POLYBAG LENG TH EXCEEDS 23" MU ST ANGLE TO FIT INT O STANDARD SIZE C ARTON LENGTH DIM ENSION 24" *DO NOT FOLD IN HALF* NOTE TO REMEMBER: *DO NOT USE PINS, CLIP S, STIFFENERS OR C ARDBOARD WITHOU T PRIOR APPROVAL. FOLDING PREPARAT IONS: *PLACE GARM ENT FACE UP *ALL C LOSURES MUST ZIP, BUTTON, SNAP ETC. FOLDING INSTRUCTI ONS: 1. GATHER WID TH OF GARMENT WIT H FINGERS, COMPRE SSING SIDES TO CEN TER. 2. SECURE AT ENDS WITH RUBBER B ANDS. 3. SHIP IN TUB E BAG. (IF THE HEAT SEALING METHOD IS USED, ALL POLYBAG S MUST THREE HALF MOON OR BUT TERFLY VENT HOLES 1/4" IN DIAMETER AN D EVENLY SPACED.)	00143	CRINKLED GARMEN TS	00004	PACKING	
	00615	FLAT FOLD SINGLE L ENGTH ON HANGER	FLAT FOLD SINGLE L ENGTH ON HANGER	00072	PANT/SHORTS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
	01152	FLAT FOLD WITH SIN GLE LENGTH (REVE RSED)	FLAT FOLD WITH SIN GLE LENGTH (REVE RSED) DETAIL: FINIS HED DIMENSIONS AF TER FOLDING: FOLD ING DIMENSIONS DE PEND ON LENGTH OF GARMENT. POLYB AG SHOULD BE ORD ERED ACCORDINGL Y. NOTES TO REMEM BER: *DO NOT USE PINS, CLIPS, STIFFEN ERS, AND CARDBOA RD WITHOUT PRIOR APPROVAL. *THE US E OF CLIPS ON BELT SIS ACCEPTABLE. FOLDING PREPARATI ONS: *PLACE GARMENT FACE UP *ALL CL OSURES MUST BUTT ON, SNAP, ZIP OR BU CKLE UNLESS OTHE RWISE STATED IN TE CH PACK. FOLDING INSTRUCTIONS: 1. FO LD GARMENT IN HALF. 2. ASSURE CROTC H EXTENSION IS TUC KED INTO FOLD. 3. PLACE THE FOLDED GARMENT INTO THE CORRECT SIZE POLYB AG AND SEAL THE POLYBAG WITH CLEAR TAPE OR HEAT SEAL. (IF THE HEAT SEALLING METHOD IS USED ALL POLYBAGS MUST HAVE THREE HALF MOON OR BUTTER FLY VENT HOLES 1/4" DIAMETER AND EVENLY SPACED.) ****** EXCEPTION: FOR DENIM OR CASUAL - DON OT USE POLYBAGS FOR PRE-PACKS	00072	PANT/SHORTS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
	00078	FLAT FOLD WITH VE RTICAL ROLL	FLAT FOLD WITH VE RTICAL ROLL	00072	PANT/SHORTS	00004	PACKING	
	00104	FLAT FOLD WITH VE RTICAL ROLL	FLAT FOLD WITH VE RTICAL ROLL	00079	MEN'S SHIRTS	00004	PACKING	
	01629	FLAT PACK	FLAT PACK LAY GAR MENT FLAT & FOLDE D AT SS. IF GARMEN T IS TOO LARGE FOR CARTON, ROLL IN HA LF ONCE AFTER PLA CING GARMENT IN C ARTON.	00078	WOMEN'S SHIRTS/BL OUSES	00004	PACKING	
	00010	FLAT PACK (SINGLE FOLD)- PKG10	FLAT PACK (SINGLE FOLD)- PKG10 PACK ED POLY BAG DIMEN SIONS MUST NOT EX CEED 23L X 16W ANT HROPOLOGIE: NO RE STRICTIONS ON POL YBAGS, FOLLOW PR OPER FOLDING AND ORDER POLYBAG AC CORDINGLY POLYBA GS SHOULD BE ORD ERED ACCORDING T O FOLDED GARMENT UTILIZING DIMENSIO NS OF STANDARD CA RTON, NO EXCESS R OOM FOR GARMENT SHIFTING. DO NOT A LLOW MORE THAN 1" OF SPACE BETWEEN EDGE OF GARMENT AND POLYBAG. SEAL THE POLYBAG WITH CLEAR TAPE OR HEA T SEAL. (IF THE HEA T SEAL.) (IF THE HEA T SUSED ALL POLYBAG GS MUST HAVE THR	00073	JACKETS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			EE HALF MOON OR B UTTERFLY VENT HOL ES 1/4" DIAMETER AN D EVENLY SPACED.) GARMENT MUST FIT! N STANDARD SIZE C ARTON NOTES TO R EMEMBER: *DO NOT USE PINS, CLIPS, ST IFFENERS OR CARD BOARD WITHOUT PRI OR APPROVAL. *TISS UE MAY BE USED ON LIGHTWEIGHT FABRI CS (I.E. SILKS, RAYO N, POLYESTER ETC.) FOLDING INSTRUCTI ONS: SEE PHOTO **** * EXCEPTION: - DO N OT USE POLYBAGS F OR PRE-PACKS					
FLET INCK. MOTOLD See a consideration of the consi	01782	FLAT PACK NO FOLD	FLAT PACK NO FOLD IF BAG EXCEEDS CA RTON DIMENSIONS, OKAY TO FOLD BAG. IT IS NOT OKAY TO F OLD GARMENT WITHI N THE BAG. NOTED T O REMEMBER: *DO N OT USE PINS, CLIPS, STIFFENERS, AND C ARDBOARD WITHOU T PRIOR APPROVAL . *THE USE OF CLIPS ON BELTS IS ACCEPT ABLE. *THE USE OF T ISSUE IS ACCEPTAB LE FOR LIGHTWEIGH T MATERIALS (I.E. RA YON OR SILK) PREPA RATIONS: *PLACE GA RMENT FACE DOWN *BUTTON, SNAP, ZIP OR BUCKLE	00071	SKIRTS	00004	PACKING	
1. LAY PLAY 1. LA	01777	FLAT PACK-SHORT S LEEVE/SLEEVELESS	FLAT PACK-SHORT S LEEVE/SLEEVELESS PLACE GARMENT IN POLYBAG FLAT. POL YBAG SHOULD BE N O MORE THAN 1" LO NGER OR WIDER TH AN GARMENT. IF GA RMENT EXCEEDS CA RTON SIZE FOLD PO LY BAG IN HALF AND TAPE CLOSED.	00078	WOMEN'S SHIRTS/BL OUSES	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
PACKING REQUIREMENT 82 100 100 100 100 100 100 100	00851	FOLDED / LIGHT VER TICAL RUMPLE	FOLDED / LIGHT VER TICAL RUMPLE FINIS HED DIMENSIONS AF TER FOLDING: FOLDI NG DIMENSIONS DEP END ON LENGTH OF GARMENT. POLYBAG SHOULD BE ORDERE D ACCORDINGLY TO ASSURE THAT GARM ENT FITS IN BAG TIG HTLY TO HOLD PACK ING TECHNIQUE. NO TE TO REMEMBER: * DO NOT USE PINS, C LIPS, STIFFENERS O R CARDBOARD WITH OUT PRIOR APPROV AL. FOLDING PREPA RATIONS: *PLACE GA RMENT FACE UP *AL L CLOSURES MUST Z IP, BUTTON, SNAP ET C. FOLDING INSTRUC TIONS: 1. FOLD IN SL EEVES TO CENTER A ND FOLD BOTTOM T O CENTER 2. LIGHT V ERTICAL SCRUNCH I NSIDE POLY BAG 3. P ACK LOOSELY IN PO LYBAG WITH 1/4" EA SE ALL AROUND BAG. "IF THE HEAT SEALI NG METHOD IS BEIN G USED, ALL POLYBA GS MUST HAVE THR EE HALF MOON OR B UTTERFLY VENT HO LES 1/4" DIAMETER A ND EVENLY SPACED. DOLMAN OR KIMONO SLEEVE TOPS	00076	KNIT TOPS/TEE SHIR TS	00004	PACKING	
dispersion of the state of the	00014	FULL CIRCLE FOLD- PKG01	FULL CIRCLE FOLD- PKG01	00071	SKIRTS	00004	PACKING	
	00983	GOHF= GARMENT O N HANGER FLAT PA CK	GOHF= GARMENT O N HANGER FLAT PAC K HANG GARMENT O N HANGER & ENCAS	00207	MGRS. ONLY	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			E IN POLYBAG. POLY BAG LENGTH MUST = MINIMUM 4" LONGER THAN FINISHED GAR MENT LENGTH. ROLL UP BAG OPENING TO FINISH 1" BELOW GA RMENT HEM AND TA PE CLOSED. MAXIMU M SINGLE LENGTH F OLD AS NEEDED TO FIT IN SPECIFIED CO NTAINER. FLAT PACK IN CARTON					
	00984	GOHH = GARMENT O N HANGER HANGING	GOHH = GARMENT O N HANGER HANGING HANG GARMENT ON HANGER & ENCASE I N POLYBAG. POLYBA G LENGTH MUST = M INIMUM 4" LONGER T HAN FINISHED GARM ENT LENGTH. ROLL U P BAG OPENING TO INISH 1" BELOW GAR MENT HEM AND TAP E CLOSED. GARMEN T HANGS IN CARTON	00207	MGRS. ONLY	00004	PACKING	
	00084	HIGH TWIST	HIGH TWIST FINISHE D DIMENSIONS AFTE R FOLDING: FOLDING DIMENSIONS DEPEN D ON LENGTH OF GA RMENT. POLYBAG S HOULD BE ORDERED ACCORDINGLY TO A SSURE THAT THE GA RMENT FITS TIGHTLY IN BAG TO HOLD PAC KING TECHNIQUE. N OTE TO REMEMBER: *DO NOT USE PINS, C LIPS, STIFFENERS O R CARDBOARD WITH OUT PRIOR APPROV AL. FOLDING PREPA RATIONS: *PLACE GA RMENT FACE UP *AL L CLOSURES MUST 2 IP, BUTTON, SNAP ET C. FOLDING INSTRUC TIONS: 1. GATHER WI DTH OF GARMENT WI TH FINGERS, COMPE ESSING SIDES TO CE NTER. 2. TWIST VERT ICALLY UNTIL GARM	00143	CRINKLED GARMEN TS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			ENT FOLDS ON ITSEL F. 3. SHIP TWISTED I N CORRECT SIZE PO LYBAG. *IF THE HEA T SEALING METHOD I S USED, ALL POLYBAGS MUST HAVE THR EE HALF MOON OR B UTTERFLY VENT HOL ES 1/4" DIAMETER AN D EVENLY SPACED.					
Annual black for the large of t	00816	LEIFSDOTTIR HEM F OLDED BACK ON HA NGER	LEIFSDOTTIR HEM F OLDED BACK ON HA NGER SHIP ON SPEC IFIED HANGER ACCO RDING TO LEIFSDOT TIR SHIPPING GUIDE . ENCASE GARMENT I N POLYBAG. POLYBA G LENGTH MUST = M INIMUM 4" LONGER T HAN FINISHED GARM ENT LENGTH. ROLL P BAG OPENING TO F INISH 1" BELOW GAR MENT HEM AND TAP E CLOSED.	00071	SKIRTS	00004	PACKING	
	00080	LIGHT RUMPLE	LIGHT RUMPLE FINIS HED DIMENSIONS AF TER FOLDING: FOLDI NG DIMENSIONS DEP END ON LENGTH OF GARMENT. POLYBAG SHOULD BE ORDERE D ACCORDINGLY TO ASSURE THAT GARM ENT FITS IN BAG TIG HTLY TO HOLD PACK ING TECHNIQUE. NO TE TO REMEMBER: * DO NOT USE PINS, C LIPS, STIFFENERS O R CARDBOARD WITH OUT PRIOR APPROV AL. FOLDING PREPA RATIONS: *PLACE GA RMENT FACE UP *AL L CLOSURES MUST Z IP, BUTTON, SNAP ET C. FOLDING INSTRUC TIONS: 1. BRING THE FOUR CORNERS OF THE GARMENT TO C ENTER IN RUMPLE. 2 . PACK LOOSELY IN P OLYBAG WITH ½" EA SE ALL AROUND BAG	00143	CRINKLED GARMEN TS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			. *IF THE HEAT SEALI NG METHOD IS BEIN G USED, ALL POLYBA GS MUST HAVE THR EE HALF MOON OR B UTTERFLY VENT HOL ES 1/4" DIAMETER AN D EVENLY SPACED.					
	01088	LIGHT RUMPLE	LIGHT RUMPLE FINIS HED DIMENSIONS AF TER FOLDING: FOLD ING DIMENSIONS DE PEND ON LENGTH OF GARMENT. POLYB AG SHOULD BE ORD ERED ACCORDINGLY TO ASSURE THAT G ARMENT FITS IN BAG TIGHTLY TO HOLD P ACKING TECHNIQUE. NOTE TO REMEMBE R: *DO NOT USE PIN S, CLIPS, STIFFENER S OR CARDBOARD W ITHOUT PRIOR APPROVAL. FOLDING PRE PARATIONS: *PLACE GARMENT FACE UP * ALL CLOSURES MUS T ZIP, BUTTON, SNA P ETC. FOLDING INS TRUCTIONS: 1. BRIN G THE FOUR CORNE RS OF THE GARMEN T TO CENTER IN RUM PLE. 2. PACK LOOSE LY IN POLYBAG WITH 1/4" EASE ALL AROU ND BAG. *IF THE HEA T SEALING METHOD I S BEING USED, ALL P OLYBAGS MUST HAV E THREE HALF MOO N OR BUTTERFLY VE NT HOLES 1/4" DIAM ETER AND EVENLY S PACED.	00075	SHIRTS/DRESSES/JU MPERS	00004	PACKING	
	00649	LIGHT RUMPLE PACK	LIGHT RUMPLE PAC K FINISHED DIMENSI ONS AFTER FOLDING : FOLDING DIMENSIO NS DEPEND ON LEN GTH OF GARMENT. P OLYBAG SHOULD BE ORDERED ACCORDI NGLY TO ASSURE TH AT GARMENT FITS IN	00076	KNIT TOPS/TEE SHIR TS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			BAG TIGHTLY TO HO LD PACKING TECHNI QUE. NOTE TO REME MBER: *DO NOT USE PINS, CLIPS, STIFFEN ERS OR CARDBOARD WITHOUT PRIOR APP ROVAL. FOLDING PR EPARATIONS: *PLAC E GARMENT FACE U P *ALL CLOSURES M UST ZIP, BUTTON, SN AP ETC. FOLDING IN STRUCTIONS: 1. BRI NG THE FOUR CORN ERS OF THE GARME NT TO CENTER IN RU MPLE. 2. PACK LOOS ELY IN POLYBAG WIT H 1/4" EASE ALL ARO UND BAG. *IF THE HE AT SEALING METHO D IS BEING USED, AL L POLYBAGS MUST H AVE THREE HALF MO ON OR BUTTERFLY V ENT HOLES 1/4" DIAM ETER AND EVENLY S PACED.					
TOTAL TOTAL STATE OF THE PARTY	01647	LONG COAT - DOUBL E FOLD	LONG COAT - DOUBL E FOLD POLYBAGS S HOULD BE ORDERED ACCORDING TO FOL DED GARMENT UTILI ZING DIMENSIONS O F STANDARD CARTO N, NO EXCESS ROO M FOR GARMENT SH IFTING. DO NOT ALL OW MORE THAN 1" O F SPACE BETWEEN E DGE OF GARMENT A ND POLYBAG. SEAL THE POLYBAG WITH C LEAR TAPE OR HEA T SEAL. (IF THE HEA T SEAL. (IF THE HEA T SEALING METHOD I S USED ALL POLYBAG SMUST HAVE THR EE HALF MOON OR B UTTERFLY VENT HOLES 1/4" DIAMETER AN D EVENLY SPACED.) GARMENT MUST FIT IN STANDARD SIZE C ARTON NOTES TO R EMEMBER: "DO NOT	00073	JACKETS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			USE PINS, CLIPS, ST IFFENERS OR CARD BOARD WITHOUT PRI OR APPROVAL. *TISS UE MAY BE USED ON LIGHTWEIGHT FABRI CS (I.E. SILKS, RAYO N, POLYESTER ETC.) FOLDING INSTRUCTI ONS: SEE PHOTO **** * EXCEPTION: - DO N OT USE POLYBAGS F OR PRE-PACKS					
TOP 1 AND	01646	LONG DRESS- DOUB LE FOLD	LONG DRESS- DOUB LE FOLD POLYBAGS SHOULD BE ORDERE D ACCORDING TO FO LDED GARMENT UTI LIZING DIMENSIONS OF STANDARD CART ON, NO EXCESS ROO M FOR GARMENT SH IFTING. DO NOT ALL OW MORE THAN 1" O F SPACE BETWEEN E DGE OF GARMENT A ND POLYBAG. SEAL T HE POLYBAG WITH C LEAR TAPE OR HEA T SEAL. (IF THE HEA T SEAL. (IF THE HEA T SEALLING METHOD I S USED ALL POLYBA GS MUST HAVE THR EE HALF MOON OR B UTTERFLY VENT HOL ES 1/4" DIAMETER AN D EVENLY SPACED.) GARMENT MUST FIT I N STANDARD SIZE C ARTON NOTES TO R EMEMBER: *DO NOT USE PINS, CLIPS, ST IFFENERS OR CARD BOARD WITHOUT PRI OR APPROVAL. *TISS UE MAY BE USED ON LIGHTWEIGHT FABRI CS (I.E. SILKS, RAYO N, POLYESTER ETC.) FOLDING INSTRUCTI ONS: SEE PHOTO	00075	SHIRTS/DRESSES/JU MPERS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
	00019	MEN'S DRESS SHIRT - PKG18	MEN'S DRESS SHIRT - PKG18	00079	MEN'S SHIRTS	00004	PACKING	
	02576	MOLDED BRA PACK ING	*FLAT PACK WITH TIS SUE BEHIND EACH C UP. *PLACE IN POLY BAG AS PHOTO *PAC K ALL CARTONS LOO SELY TO PREVENT C RUSHING THE CUP	00176	BRAS	00004	PACKING	
	00973	NO LENGTH FOLD(EX . PLEATS OR ZIPPER DWN CF)- PKG02	NO LENGTH FOLD(E X. PLEATS OR ZIPPE R DWN CF)- PKG02 F INISHED DIMENSION S AFTER FOLDING: F OLDING DIMENSIONS DEPEND ON LENGTH OF GARMENT. POLY BAG SHOULD BE OR DERED ACCORDINGL Y. NOTED TO REMEM BER: *DO NOT USE PI NS, CLIPS, STIFFENE RS, AND CARDBOAR D WITHOUT PRIOR A PPROVAL. *THE USE OF CLIPS ON BELTS I S ACCEPTABLE. *THE USE OF TISSUE IS A CCEPTABLE FOR LIG HTWEIGHT MATERIA LS (I.E. RAYON OR SI LK) FOLDING PREPA RATIONS: *PLACE GA RMENT FACE DOWN *BUTTON, SNAP, ZIP OR BUCKLE FOLDING INSTRUCTIONS: 1. F OLD GARMENT IN HA LF. 2. PLACE THE FO LDED GARMENT INT O THE CORRECT SIZ E POLYBAG AND SEA L THE POLYBAG WIT H CLEAR TAPE OR H EAT SEAL. (IF THE HE AT SEAL. (IF THE HE AT SEALING METHOD	00207	MGRS. ONLY	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			IS USED ALL POLYBA GS MUST HAVE THR EE HALF MOON OR B UTTERFLY VENT HOL ES 1/4" DIAMETER AN D EVENLY SPACED.)					
	00008	NO LENGTH FOLD- P KG05	NO LENGTH FOLD- P KG05 FINISHED DIME NSIONS AFTER FOLD ING: FOLDING DIMEN SIONS DEPEND ON L ENGTH OF GARMEN T. POLYBAG SHOULD BE ORDERED ACCOR DINGLY. NOTED TO R EMEMBER: *DO NOT USE PINS, CLIPS, STI FFENERS AND CARD BOARD WITHOUT PR IOR APPROVAL. *THE USE OF CLIPS ON BE LTS IS ACCEPTABLE. *THE USE OF TISSUE IS ACCEPTABLE FOR LIGHTWEIGHT MATE RIALS (I.E. RAYON O R SILK). FOLDING PR EPARATIONS: *PLAC E GARMENT FACE U P *ALL CLOSURES M UST BUTTON, SNAP, ZIP OR BUCKLE UNL ESS OTHERWISE ST ATED IN TECH PACK . FOLDING INSTRUC TIONS: 1. FOLD GAR MENT IN HALF. 2. AS SURE CROTCH EXTE NSION IS TUCKED IN TO FOLD. 3. PLACE T HE FOLDED GARMEN T INTO THE CORREC T SIZE POLYBAG AN D SEAL THE POLYBA G WITH CLEAR TAPE OR HEAT SEAL. (IF T HE HEAT SEAL ING T HE HEAT SEAL ING T HE THOD IS USED ALL POLYBAGS MUST HA VE THREE HALF MOO N OR BUTTERFLY VE NT HOLES 1/4" DIAM ETER AND EVENLY S PACED.) ****** EXCEP TION: FOR DENIM OR CASUAL - DO NOT U	00072	PANT/SHORTS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem	Construction Elem ent Desc	Status
			SE POLYBAGS FOR P RE-PACKS					
	00761	NO SLEEVE CREASE	NO SLEEVE CREASE	00076	KNIT TOPS/TEE SHIR TS	00004	PACKING	
The state of the s	00760	NO SLEEVE CREASE WITH RUFFLE	NO SLEEVE CREASE WITH RUFFLE	00076	KNIT TOPS/TEE SHIR TS	00004	PACKING	
	PACKING	PACKING		PACKING	PACKING	PACKING	PACKING PLACEHOL DER	
	01622	PACKING NOTES	PACKING NOTES	00226	PACKING NOTES	00004	PACKING	
	00435	PANT TWISTED BRO OMSTITCK	PANT TWISTED BRO OMSTITCK FINISHED DIMENSIONS AFTER FOLDING: FOLDING D IMENSIONS DEPEND ON LENGTH OF GAR MENT. POLYBAG SH OULD BE ORDERED ACCORDINGLY TO A SSURE THAT GARME NT FITS IN BAG TIGH TLY TO HOLD PACKI NG TECHNIQUE. NOT E TO REMEMBER: *D O NOT USE PINS, CL IPS, STIFFENERS OR CARDBOARD WITHO UT PRIOR APPROVA L. FOLDING PREPAR ATIONS: *PLACE GAR MENT FACE UP *ALL CLOSURES MUST ZIP , BUTTON, SNAP ETC . FOLDING INSTRUCT IONS: 1. GATHER WID TH OF GARMENT WIT H FINGERS, COMPRE SSING SIDES TO CEN TER. 2. TWIST VERTI CALLY; DO NOT FOL	00072	PANT/SHORTS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			D. 3. SHIP TWISTED I N TUBE BAG. *IF THE HEAT SEALING METH OD IS BEING USED, A LL POLYBAGS MUST HAVE THREE HALF M OON OR BUTTERFLY VENT HOLES 1/4" DIA METER AND EVENLY SPACED.					
PLEASE REPLACE THIS IMAGE WITH THE IMAGE YOU WOULD LIKE TO USE	PKGPH	PLACEHOLDER FOR PACKING INSTRUCT IONS	THIS IS TO BE USED FOR RARELY USED, ONE OFF PACKING IN STRUCTIONS THAT A RE NOT APART OF THE LIBRARY. PLEAS E REPLACE THIS TEX T WITH THE DESCRIPTION YOU WISH TO USE. PLEASE ALSO U PLOAD A CORRESPO NDING IMAGE BY SE LECTING "R" UNDER THE EXISTING ATTA CHMENT. IF YOU WIL L USE THIS ITEM MO RE THAN ONCE, PLE ASE CONTACT JESSI CA VINCENT TO HAV E IT ADDED TO THE L IBRARY.	00226	PACKING NOTES	PACKING	PACKING PLACEHOL DER	APPR
Manual resource in Automotive in Contract of Manual resource i	01643	PLEATED SKIRT NO FOLD AFTER POLYB AG	PLEATED SKIRT NO F OLD AFTER POLYBA G ENCASE GARMEN T IN POLYBAG. POLY BAG LENGTH MUST = MINIMUM 4" LONGER THAN FINISHED GAR MENT LENGTH. ROLL UP BAG OPENING TO FINISH 1" BELOW GA RMENT HEM AND TA PE CLOSED. DO NOT FOLD. ****THIS MAY R EQUIRE A LARGER C ARTON, PLEASE ALE RT PRODUCTION. * H OLD PLEATS IN PLAC E WITH A SOFT BAST E STITCH/ SEE SKET CH. * INSERT INTO P OLYBAG FLAT AND P LEATS LAYING FLAT SEAL POLYBAG, MUS T ADD CLIPS TO WAI	00071	SKIRTS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			ST TO PREVENT SKI RT FROM SHIFTING					
The same is a small or sold to	01723	PLEATED SKIRT SIN GLE FOLD AFTER PO LYBAG	PLEATED SKIRT SIN GLE FOLD AFTER PO LYBAG ENCASE GAR MENT IN POLYBAG. POLYBAG LENGTH MU ST = MINIMUM 4" LO NGER THAN FINISHE D GARMENT LENGTH . ROLL UP BAG OPEN ING TO FINISH 1" BELOW GARMENT HEM A ND TAPE CLOSED. DO NOT FOLD. ****THI S MAY REQUIRE A LA RGER CARTON, PLEA SE ALERT PRODUCT ION. * HOLD PLEATS IN PLACE WITH A SO FT BASTE STITCH/S EE SKETCH. * INSER T INTO POLYBAG FL AT AND PLEATS LAYING FLAT SEAL POLY BAG, MUST ADD CLIP S TO WAIST TO PRE VENT SKIRT FROM S HIFTING	00071	SKIRTS	00004	PACKING	
	00009	QUADRUPLE LENGT H FOLD- PKG08	QUADRUPLE LENGT H FOLD- PKG08	00072	PANT/SHORTS	00004	PACKING	
	00016	QUADRUPLE LENGT H FOLD- PKG12	QUADRUPLE LENGT H FOLD- PKG12	00074	ROBES	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
	00017	QUADRUPLE LENGT H FOLD- PKG13	QUADRUPLE LENGT H FOLD- PKG13 POLY BAGS SHOULD BE O RDERED ACCORDIN G TO FOLDED GARM ENT UTILIZING DIME NSIONS OF STANDA RD CARTON, NO EXC ESS ROOM FOR GAR MENT SHIFTING. DO NOT ALLOW MORE T HAN 1" OF SPACE BE TWEEN EDGE OF GA RMENT AND POLYBA G. SEAL THE POLYBA G WITH CLEAR TAPE OR HEAT SEAL. (IF T HE HEAT SEALING M ETHOD IS USED ALL POLYBAGS MUST HA VE THREE HALF MOO N OR BUTTERFLY VE NT HOLES 1/4" DIAME TER AND EVENLY SP ACED.) GARMENT MU ST FIT IN STANDARD SIZE CARTON NOTES TO REMEMBER: *DO NOT USE PINS, CLIPS , STIFFENERS OR CA RDBOARD WITHOUT PRIOR APPROVAL. *T ISSUE MAY BE USED ON LIGHTWEIGHT FA BRICS (I.E. SILKS, RA YON, POLYESTER ET C.) FOLDING INSTRU CTIONS: SEE PHOTO	00075	SHIRTS/DRESSES/JU MPERS	00004	PACKING	
3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3	00880	ROLL / FLAT PACK B ODICE WITH BONING	ROLL / FLAT PACK B ODICE WITH BONING USE FOR ROLL PACK GARMENTS WITH BO NING IN BODICE	00075	SHIRTS/DRESSES/JU MPERS	00004	PACKING	
	02575	ROLL CUFF	SHIP WITH CUFF/ VE NT UNBUTTONED AN D ROLLED 1X, 2X, 3X	00010	CUFF	00004	PACKING	APPROVE

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem	Construction Elem ent Desc	Status
TISSUE .	00169	ROLL PACK	ROLL PACK	00073	JACKETS	00004	PACKING	
	01118	ROLL PACK (NO TIS SUE)	ROLL PACK (NO TISS UE) FINISHED DIMEN SIONS AFTER FOLDI NG: FOLDING DIMEN SIONS DEPEND ON L ENGTH OF GARMEN T. POLYBAG SHOULD BE ORDERED ACCOR DINGLY. POLYBAG SHOULD FIT TIGHTLY ARO UND GARMENT NOTE STO REMEMBER: *DO NOT USE PINS, STI FFENERS, TISSUE AND CARDBOARD WITH OUT PRIOR APPROVAL. FOLDING PREPA RATIONS: *ALL CLOS URES MUST BE BUTT ON, ZIP, SNAP ECT. THIS INCLUDES ALL COLLAR BUTTONS *PLACE GARMENT FACE DOWN FOLDING INST RUCTIONS: 1. FOLD THE RIGHT SIDE OVER ON THE FOLD LINE 2. FOLD THE SLEEVE BACK AND DOWN TO LINE UP WITH FOLDED EDGE. 3. REPEAT STEPS FOR LEFT SIDE. 4. ROLL GARMENT FROM THE BOTTOM TO THE TOP IN A LOO SE ROLL. 5. PLACE THE FOLDED/ROLLED GARMENT INTO THE CORRECT SIZE POLYBAG AND SEAL THE POLYBAG WITH CLEAR TAPE OR HEAT SEAL (IF THE HEAT SEAL (IF THE HEAT SEAL ING METHOD IS USED-ALL POLYBAGS MUST HAVE THREE HALF MOONS OR BUTTE	00073	JACKETS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			RFLY VENT HOLES 1/ 4" DIAMETER AND EV ENLY SPACED.)					
1. 2 3. 4.	01035	ROLL PACK BODICE WITH BONING	ROLL PACK BODICE WITH BONING USE F OR ROLL PACK GAR MENTS WITH BONIN G IN BODICE	00075	SHIRTS/DRESSES/JU MPERS	00004	PACKING	
2. 3. Name of the state of the	01038	ROLL PACK CAMI	ROLL PACK CAMI	00078	WOMEN'S SHIRTS/BL OUSES	00004	PACKING	
3. 4.	01029	ROLL PACK WITH BE ND TO FIT CARTON	ROLL PACK WITH BE ND TO FIT CARTON U SE FOR ROLL PACK GARMENTS THAT CA N HAVE BEND	00075	SHIRTS/DRESSES/JU MPERS	00004	PACKING	
1. 2. 3. 1	01037	ROLL PACK-DRESS WITH SLEEVES	ROLL PACK-DRESS WITH SLEEVES FINIS HED DIMENSIONS AF TER FOLDING/ROLLI NG: DEPENDS ON TH E LENGTH OF THE G ARMENT. POLYBAG S IZE: DO NOT ALLOW MORE THAN 1" OF S PACE BETWEEN EDG E OF GARMENT AND POLYBAG. NOTES TO REMEMBER: *DO NO T USE PINS, CLIPS, S TIFFENERS OR CARD BOARD WITHOUT PR IOR APPROVAL. *TIS SUE MAY BE USED O N LIGHTWEIGHT FAB RICS (I.E. SILKS,RAY ON, POLYESTER ECT .) FOLDING/ROLLING PREPARATIONS: *PL ACE GARMENT FACE	00207	MGRS. ONLY	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			DOWN *ALL CLOSUR ES MUST BUTTON, Z IP, SNAP ECT. FOLD ING/ROLLING INSTRU CTIONS: 1. FOLD THE LEFT & RIGHT SLEEV ES OVER BODY/ SEE SKETCH 2. ROLL GA RMENT FROM LEFT S IDE TO RIGHT SIDE I N A LOOSE ROLL. 3. PLACE ROLLED GAR MENT INTO CORREC T SIZE POLYBAG AN D SEAL THE POLYBAG G WITH CLEAR TAPE OR HEAT SEAL. (IF T HE HEAT SEALING M ETHOD IS USED ALL POLYBAGS MUST HA VE THREE HALF MO O OR BUTTERFLY VE NT HOLES 1/4" DIAM ETER AND EVENLY S PACED.)					
	01036	ROLL PACK-SLV- DR ESS W/ BEND	ROLL PACK-SLV- DR ESS W/ BEND FINISH ED DIMENSIONS AFT ER FOLDING/ROLLIN G: DEPENDS ON THE LENGTH OF THE GAR MENT. POLYBAG SIZ E: DO NOT ALLOW M ORE THAN 1" OF SPA CE BETWEEN EDGE OF GARMENT AND P OLYBAG. NOTES TO REMEMBER: 'DO NO T USE PINS, CLIPS, S TIFFENERS OR CARD BOARD WITHOUT PR IOR APPROVAL. *TIS SUE MAY BE USED O N LIGHTWEIGHT FAB RICS (I.E. SILKS, RAY ON, POLYESTER ECT .) FOLDING/ROLLING PREPARATIONS: *PL ACE GARMENT FACE DOWN *ALL CLOSUR ES MUST BUTTON, Z IP, SNAP ECT. FOLDI NG/ROLLING INSTRU CTIONS: 1. FOLD THE LEFT & RIGHT SLEEV ES OVER BODY/ SEE SKETCH 2. ROLL GA	00075	SHIRTS/DRESSES/JU MPERS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			RMENT FROM LEFT S IDE TO RIGHT SIDE I N A LOOSE ROLL. 3. PLACE ROLLED GAR MENT INTO CORREC T SIZE POLYBAG AN D SEAL THE POLYBA G WITH CLEAR TAPE OR HEAT SEAL. (IF T HE HEAT SEALING M ETHOD IS USED ALL POLYBAGS MUST HA VE THREE HALF MO O OR BUTTERFLY VE NT HOLES 1/4" DIAM ETER AND EVENLY S PACED.)					
	01393	ROLL WITH TIE / CAS UAL SHIRTS	ROLL WITH TIE / CAS UAL SHIRTS TIE - US E SCRAP FABRIC, CA N BE SELF SELVEDG E OF FABRIC, EXPO SED RAW EDGE IS A CCEPTABLE, CAN JO IN PEICES IF NEEDE D, TIE SHOULD BE 3 /4" TO 1" WIDE, SHO ULD BE TIED WITH SI NGLE 2" LOOP AND 1 " ENDS	00079	MEN'S SHIRTS	00004	PACKING	
SDET 1 SOLD A STATE OF THE STAT	01827	ROMPER DOUBLE F OLD	ROMPER DOUBLE F OLD POLYBAGS SHO ULD BE ORDERED A CCORDING TO FOLD ED GARMENT UTILIZ ING DIMENSIONS OF STANDARD CARTON, NO EXCESS ROOM F OR GARMENT SHIFT ING. DO NOT ALLOW MORE THAN 1" OF SP ACE BETWEEN EDGE OF GARMENT AND P OLYBAG. SEAL THE P OLYBAG. SEAL THE P OLYBAG WITH CLEA R TAPE OR HEAT SEA LING METHOD IS USE D ALL POLYBAGS MU ST HAVE THREE HAL F MOON OR BUTTER FLY VENT HOLES 1/4 " DIAMETER AND EV ENLY SPACED.) GAR MENT MUST FIT IN S TANDARD SIZE CART ON NOTES TO REME	00075	SHIRTS/DRESSES/JU MPERS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			MBER: *DO NOT USE PINS, CLIPS, STIFFE NERS OR CARDBOAR D WITHOUT PRIOR A PPROVAL. *TISSUE M AY BE USED ON LIGH TWEIGHT FABRICS (I. E. SILKS, RAYON, PO LYESTER ETC.) FOLD ING INSTRUCTIONS: SEE PHOTO					
Title 1 (1992) A region of the second of the	01825	ROMPER IN BAG, DO UBLE FOLD	ROMPER IN BAG, DO UBLE FOLD POLYBA GS SHOULD BE ORD ERED ACCORDING T O FOLDED GARMENT UTILIZING DIMENSIO NS OF STANDARD CA RTON, NO EXCESS R OOM FOR GARMENT SHIFTING. DO NOT A LLOW MORE THAN 1" OF SPACE BETWEEN EDGE OF GARMENT AND POLYBAG. SEAL THE POLYBAG WITH CLEAR TAPE OR HEA T SEAL. (IF THE HEA T SEAL. (IF THE HEA T SEALING METHOD I S USED ALL POLYBA GS MUST HAVE THR EE HALF MOON OR B UTTERFLY VENT HOL ES 1/4" DIAMETER AN D EVENLY SPACED.) GARMENT MUST FIT I N STANDARD SIZE C ARTON NOTES TO R EMEMBER: *DO NOT USE PINS, CLIPS, ST IFFENERS OR CARD BOARD WITHOUT PRI OR APPROVAL. *TISS UE MAY BE USED ON LIGHTWEIGHT FABRI CS (I.E. SILKS, RAYO N, POLYESTER ETC.) FOLDING INSTRUCTI ONS: SEE PHOTO	00075	SHIRTS/DRESSES/JU MPERS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem	Construction Elem ent Desc	Status
	00231	RUMPLE PANT	RUMPLE PANT	00072	PANT/SHORTS	00004	PACKING	
	00240	SCRUNCH PACK PA	SCRUNCH PACK PAN T FOLDING DIMENSI ONS DEPEND ON LE NGTH OF GARMENT. POLYBAG SHOULD B E ORDERED ACCOR DINGLY. NOTES TO R EMEMBER: *DO NOT USE PINS, CLIPS, STI FFENERS, AND CARD BOARD WITHOUT PR IOR APPROVAL. *THE USE OF CLIPS ON BE LTS IS ACCEPTABLE. *THE USE OF TISSUE IS ACCEPTABLE FOR LIGHTWEIGHT MATE RIALS (I.E. RAYON O R SILK) FOLDING PR EPARATIONS: *PLAC E GARMENT FACE U P *ALL CLOSURES M UST BUTTON, SNAP, ZIP OR BUCKLE UNL ESS OTHERWISE ST ATED IN TECH PACK. FOLDING (SCRUNCH ING) INSTRUCTIONS: 1. SCRUNCH EACH P ANT LEG UP FROM H EM TO CROTCH 2. FO LD PANT IN HALF (BA CK OF PANT SHOULD BE EXPOSED AFTER FOLDING) 3. PLACE T HE SCRUNCHED & F OLDED GARMENT IN TO A TIGHT FITTING POLYBAG AND SEAL THE POLYBAG WITH CLEAR TAPE OR HEA T SEALING METHOD I S USED ALL POLYBA GS MUST HAVE THR EE HALF MOON OR B UTTERFLY VENT HOL	00072	PANT/SHORTS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			ES 1/4" DIAMETER AN D EVENLY SPACED.)					
SAMP MINICA ROS ROX.	01803	SHIRT VERTICAL RO LL PACK	SHIRT VERTICAL RO LL PACK FINISHED D IMENSIONS AFTER F OLDING/ROLLING: DE PENDS ON THE LENG TH OF THE GARMEN T. POLYBAG SIZE: DO NOT ALLOW MORE T HAN 1" OF SPACE BE TWEEN EDGE OF GA RMENT AND POLYBA G. NOTES TO REMEM BER: "DO NOT USE P INS, CLIPS, STIFFEN ERS OR CARDBOAR D WITHOUT PRIOR A PPROVAL. *TISSUE M AY BE USED ON LIGH TWEIGHT FABRICS (I LS. SILKS,RAYON, PO LYESTER ECT.) FOLD ING/ROLLING PREPA RATIONS: *PLACE G ARMENT FACE DOW N *ALL CLOSURES M UST BUTTON, ZIP, SN AP ECT. FOLDING/RO LLING INSTRUCTION S: 1. FOLD THE LEFT & RIGHT SIDE OF GA RMENT OVER ON TH E FOLD LINES 2. ROL L GARMENT FROM T HE TOP TO THE BOT TOM IN A LOOSE RO LL. 3. PLACE ROLLED GARMENT INTO COR RECT SIZE POLYBAG AND SEAL THE POLY BAG WITH CLEAR TA PE OR HEAT SEALING METHOD IS USED AL L POLYBAGS MUST H AVE THREE HALF MO ON OR BUTTERFLY V ENT HOLES 1/4" DIAM ETER AND EVENLY S PACED.)	00078	WOMEN'S SHIRTS/BL OUSES	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
	00272	SHIRT-VERTICAL RO LL WITH COLLAR DO WN & BUTTONED	SHIRT-VERTICAL RO LL WITH COLLAR DO WN & BUTTONED FI NISHED DIMENSION S AFTER FOLDING: F OLDING DIMENSION S DEPEND ON LENG TH OF GARMENT. PO LYBAG SHOULD BE O RDERED ACCORDIN GLY. POLYBAG SIZE: POLYBAG SHOULD F IT TIGHTLY AROUND GARMENT NOTES TO REMEMBER: *DO NO T USE PINS, STIFFEN ERS AND CARDBOAR D WITHOUT PRIOR A PPROVAL. FOLDING PREPARATIONS: *AL L CLOSURES MUST B E BUTTON, ZIP, SNA P ECT. THIS INCLUD ES ALL COLLAR BUT TONS *PLACE GARM ENT FACE DOWN FO LDING INSTRUCTION S: 1. FOLD THE RIGH T SIDE OVER ON THE FOLD LINE 2. FOLD T HE SLEEVE BACK AN D DOWN TO LINE UP WITH FOLDED EDGE. 3. REPEAT STEPS FO R LEFT SIDE. 4. ROLL GARMENT FROM TH E BOTTOM TO THE T OP IN A LOOSE ROLL 5. PLACE THE FOLD ED/ROLLED GARMEN T INTO THE CORREC T SIZE POLYBAG AN D SEAL THE POLYBA G WITH CLEAR TAPE OR HEAT SEAL. (IF T HE HEAT SEAL.ING M ETHOD IS USED-ALL POLYBAGS MUST HA VE THREE HALF MOO NS OR BUTTERFLY V ENT HOLES 1/4" DIAM ETER AND EVENLY S PACED.)	00079	MEN'S SHIRTS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem	Construction Elem ent Desc	Status
	00892	SINGLE FOLD PACK	SINGLE FOLD PACK F INISHED DIMENSION S AFTER FOLDED: AP PROXIMATE FOLDED DIMENSION SHOULD BE 10"X12" OR 10"X14 ". NOTED TO REMEM BER: *DO NOT USE P INS, CLIPS, STIFFEN ERS, AND CARDBOA RD WITHOUT PRIOR APPROVAL. *THE US E OF CLIPS ON BELT S IS ACCEPTABLE. *T HE USE OF TISSUE IS ACCEPTABLE FOR LI GHTWEIGHT MATER IALS (I.E. RAYON OR SILK) FOLDING PREP ARATIONS: *PLACE G ARMENT FACE DOW N *BUTTON, SNAP, ZI P OR BUCKLE FOLDI NG INSTRUCTIONS: 1 . FOLD SIDES OF GA RMENT IN LENGTHWI SE. 2. FOLD BOTTOM OF SKIRT UP TO THE TOP OF SKIRT. 3. PL ACE THE FOLDED GA RMENT INTO THE CO RRECT SIZE POLYBA G AND SEAL THE PO LYBAG WITH CLEAR TAPE OR HEAT SEAL . (IF THE HEAT SEAL . (IF THE HEAT SEAL . (IF THE HEAT SEAL . WOMETHOD IS USED ALL POLYBAGS MUS T HAVE THREE HALF MOON OR BUTTERFL Y VENT HOLES1/4" DI AMETER AND EVENL Y SPACED.)	00071	SKIRTS	00004	PACKING	
	01354	SINGLE LENGTH FO LD	SINGLE LENGTH FOL D POLYBAGS SHOUL D BE ORDERED ACC ORDING TO FOLDED GARMENT UTILIZING DIMENSIONS OF STA NDARD CARTON, NO EXCESS ROOM FOR GARMENT SHIFTING . DO NOT ALLOW MO RE THAN 1" OF SPAC E BETWEEN EDGE O F GARMENT AND PO LYBAG. SEAL THE PO	00078	WOMEN'S SHIRTS/BL OUSES	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			LYBAG WITH CLEAR TAPE OR HEAT SEAL . (IF THE HEAT SEAL) . ALL POLYBAGS MUS T HAVE THREE HALF MOON OR BUTTERFL Y VENT HOLES 1/4" D IAMETER AND EVENL Y SPACED.) GARMEN T MUST FIT IN STAND ARD SIZE CARTON N OTES TO REMEMBER : *DO NOT USE PINS . CLIPS, STIFFENERS OR CARDBOARD WIT HOUT PRIOR APPRO VAL. *TISSUE MAY BE USED ON LIGHTWEIG HT FABRICS (I.E. SILK S, RAYON, POLYEST ER ETC.) FOLDING IN STRUCTIONS: SEE P HOTO DO NOT FOLD THROUGH SHOULDE RS UNLESS SHOULD ERS EXCEED 16".					
	01757	SINGLE LENGTH FO LD - NO CREASE SL EEVE	SINGLE LENGTH FO LD - NO CREASE SL EEVE	00078	WOMEN'S SHIRTS/BL OUSES	00004	PACKING	
	00013	SINGLE LENGTH FOL D- PKG06	SINGLE LENGTH FOL D- PKG06	00072	PANT/SHORTS	00004	PACKING	
	00015	SINGLE LENGTH FOL D- PKG15	SINGLE LENGTH FOL D- PKG15	00076	KNIT TOPS/TEE SHIR TS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem	Construction Elem ent Desc	Status
	00007	SINGLE LENGTH FOL D- PKG16	SINGLE LENGTH FOL D- PKG16	00077	LG SLEEVE KNIT TOP /LGHTWGHT QUILTE D JACKET	00004	PACKING	
fold in a sides, rail ge from hern and gust in a poly hing free closed	00855	SKIRT HORIZONTAL ROLL PACK	SKIRT HORIZONTAL ROLL PACK FINISHE D DIMENSIONS AFTE R FOLDING: FOLDING DIMENSIONS DEPEN D ON LENGTH OF GA RMENT. POLYBAG S HOULD BE ORDERED ACCORDINGLY. NOT ED TO REMEMBER: *DO NOT USE PINS, C LIPS, STIFFENERS, A ND CARDBOARD WIT HOUT PRIOR APPRO VAL. *THE USE OF C LIPS ON BELTS IS AC CEPTABLE. *THE USE OF TISSUE IS ACCEP TABLE FOR LIGHTWE IGHT MATERIALS (I.E. RAYON OR SILK) FO LDING PREPARATION S: LAY GARMENT FL AT. FOLDING INSTRU CTIONS: 1. FOLD SID ES INWARD AS SKET CH 2. ROLL UP FROM HEM AS SKETCH 3. P LACE THE ROLLED G ARMENT INTO THE C ORRECT SIZE POLYB AG AND SEAL THE P OLYBAG WITH CLEAR TAPE OR HEAT SEAL (IF THE HEAT SEAL ING METHOD IS USED ALL POLYBAGS WITH CLEAR TAPE OR HEAT SEAL ING METHOD IS USED ALL POLYBAGS MU ST HAVE THREE HAL F MOON OR BUTTER FLY VENT HOLES 1/4 " DIAMETER AND EVENLY SPACED.)	00071	SKIRTS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem	Construction Elem ent Desc	Status
STATE OF THE PROPERTY OF THE P	01638	SKIRT: SINGLE FOLD AFTER POLYBAG -NO CREASE	SKIRT: SINGLE FOLD AFTER POLYBAG -NO CREASE ENCASE GA RMENT IN POLYBAG. POLYBAG LENGTH M UST = MINIMUM 4" L ONGER THAN FINISH ED GARMENT LENGT H. ROLL UP BAG OPE NING TO FINISH 1" B ELOW GARMENT HE M AND TAPE CLOSE D. DO NOT FOLD. * F OLD BAG IN HALF AN D TAPE TOGETHER * USE FOR SKIRTS TO MINIMIZE FOLDED C REASE	00071	SKIRTS	00004	PACKING	
	2023	SLEEVE FOLDED FO R SHIPPING	- SLEEVES MUST BE ROLLED 3 TIMES FO R SHIPPING. SLEEVE PLACKET SHOULD B E UNBUTTONED.	00078	WOMEN'S SHIRTS/BL OUSES	00004	PACKING	
METALOGUE DE LA CONTROLLA DE	01637	SOFT PLEATED SKIR T:SINGLE FOLD AFTE R POLYBAG	SOFT PLEATED SKIR T:SINGLE FOLD AFTE R POLYBAG ENCASE GARMENT IN POLYB AG. POLYBAG LENGT H MUST = MINIMUM 4 "LONGER THAN FINI SHED GARMENT LEN GTH. ROLL UP BAG O PENING TO FINISH 1" BELOW GARMENT H EM AND TAPE CLOS ED. * HOLD PLEATS I N PLACE WITH A SO FT BASTE STITCH/ S EE SKETCH. * INSER T INTO POLYBAG FL AT AND PLEATS LAY ING FLAT	00071	SKIRTS	00004	PACKING	
	SPI	SPI		SPI	SPI	SPI	SPECIAL PACKING IN STRUCTIONS	
THE ADMINISTRATION OF THE PROPERTY OF THE PROP	01383	STANDARD CLOTH	STANDARD CLOTH S EE PHOTO FOR SPE CIFICS	00072	PANT/SHORTS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem	Construction Elem ent Desc	Status
15 to 16 to	00320	STANDARD PANTY 3 FOLD & PACK	STANDARD PANTY 3 FOLD & PACK	00177	PANTY	00004	PACKING	
	00899	STRAP OR STRAPLE SS DRESS SINGLE LE NGTH FOLD	STRAP OR STRAPLE SS DRESS SINGLE LE NGTH FOLD POLYBA GS SHOULD BE ORD ERED ACCORDING T O FOLDED GARMENT UTILIZING DIMENSIO NS OF STANDARD CA RTON, NO EXCESS R OOM FOR GARMENT SHIFTING. DO NOT A LLOW MORE THAN 1" OF SPACE BETWEEN EDGE OF GARMENT AND POLYBAG. SEAL THE POLYBAG WITH CLEAR TAPE OR HEA T SEAL. (IF THE HEA T SEAL. (IF THE HEA T SEALING METHOD I S USED ALL POLYBA GS MUST HAVE THR EE HALF MOON OR B UTTERFLY VENT HOL ES 1/4" DIAMETER AN D EVENLY SPACED.) GARMENT MUST FIT N STANDARD SIZE C ARTON NOTES TO R EMEMBER: *DO NOT USE PINS, CLIPS, ST IFFENERS OR CARD BOARD WITHOUT PRI OR APPROVAL. *TISS UE MAY BE USED ON LIGHTWEIGHT FABRI CS (I.E. SILKS, RAYO N, POLYESTER ETC.) FOLDING INSTRUCTI ONS: SEE PHOTO US E FOR STRAPPY & ST RAPLESS DRESSES	00075	SHIRTS/DRESSES/JU MPERS	00004	PACKING	

C	Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
		00081	SUPER RUMPLE WIT H SELF TIE	SUPER RUMPLE WIT H SELF TIE FINISHED DIMENSIONS AFTER FOLDING: FOLDING DIMENSIONS DEPEND ON LENGTH OF GAR MENT. POLYBAG SHOULD BE ORDERED ACCORDINGLY TO A SSURE THAT GARME NT FITS TIGHTLY IN B AG TO HOLD PACKIN G TECHNIQUE. NOTE TO REMEMBER: *DO NOT USE PINS, CLIP S, STIFFENERS OR C ARDBOARD WITHOU T PRIOR APPROVAL. FOLDING PREPARATI ONS: *PLACE GARME NT FACE UP *ALL CL OSURES MUST ZIP, B UTTON, SNAP ETC. FOLDING INSTRUCTIO NS: 1. BRING THE FO UR CORNERS OF THE GARMENT TO CEN TER IN RUMPLE. 2. T IE GARMENT TO CEN TER IN RUMPLE. 2. T IE GARMENT TO CEN TER IN RUMPLE. 2. T IE GARMENT TO CEN TER IN RUMPLE. 2. T IE GARMENT TO CEN TER IN RUMPLE. 2. T IE GARMENT SHOULD BE HIGHLY COMPRE SSED. 3. SHIP IN COR RECT SIZE POLYBAG. *IF USING THE HEA T SEALING METHOD, ALL POLYBAGS MUS T HAVE THREE HALF MOON OR BUTTERFL Y VENT HOLES 1/4" D IAMETER AND EVENL Y SPACED.	00143	CRINKLED GARMEN TS	00004	PACKING	
STE	MCX 1	00686	SWEATER - LONG SL EEVE	SWEATER - LONG SL EEVE PACKED POLY BAG DIMENSIONS M UST NOT EXCEED 23 L X 16W ***** EXCEPT ION - DO NOT USE P OLYBAGS FOR PRE- PACKS	00187	SWEATERS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
3 3	00684	SWEATER-SHORT, 3	SWEATER-SHORT, 3/ 4 PACKED POLY BAG DIMENSIONS MUST N OT EXCEED 23L X 16 W ***** EXCEPTION - DO NOT USE POLYBA GS FOR PRE-PACKS	00187	SWEATERS	00004	PACKING	
	00653	TROUSER FOLD NO L ENGHT FOLD ON HA NGER	TROUSER FOLD NO L ENGHT FOLD ON HA NGER	00072	PANT/SHORTS	00004	PACKING	
	00614	TROUSER FOLD SIN GLE LENGTH ON HA NGER	TROUSER FOLD SIN GLE LENGTH ON HA NGER	00072	PANT/SHORTS	00004	PACKING	
	00077	TROUSER FOLD WIT H VERICAL ROLL	TROUSER FOLD WIT H VERICAL ROLL	00072	PANT/SHORTS	00004	PACKING	
	00020	TROUSER FOLD- PK G09	TROUSER FOLD- PK G09	00072	PANT/SHORTS	00004	PACKING	

0	verview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem	Construction Elem ent Desc	Status
		00982	TROUSER PACK(EXA MPLE JACKET W/ CF ZIPPER)- PKG11	TROUSER PACK(EXA MPLE JACKET W/ CF ZIPPER)- PKG11 FINI SHED DIMENSIONS A FTER FOLDING: FOL DING DIMENSIONS D EPEND ON LENGTH OF GARMENT. POLY BAG SHOULD BE OR DERED ACCORDING LY. NOTED TO REME MBER: *DO NOT USE PINS, CLIPS, STIFFEN ERS OR CARDBOARD WITHOUT PRIOR APP ROVAL. FOLDING PR EPARATIONS: -PLAC E GARMENT FACE D OWNALL CLOSURE S MUST ZIP, BUTTON , SNAP ETC. FOLDIN G INSTRUCTIONS: 1. FOLD GARMENT IN H ALF LENGTHWISE. 2. FOLD SLEEVES ACR OSS AND THEN DOW N ALONG LENGTH O F BODY. 3. PLACE THE FOLDED GARMEN T INTO THE CORREC T SIZE POLYBAG AN D SEAL THE POLYBA G WITH CLEAR TAPE OR HEAT SEAL. (IF T HE HEAT SEALING M ETHOD IS USED ALL POLYBAGS MUST HA VE THREE HALF MOO N OR BUTTERFLY VE NT HOLES 1/4" DIAM ETER AND EVENLY S PACED.)	00207	MGRS. ONLY	00004	PACKING	
		01716	TUBE TOP SINGLE LE NGTH FOLD- PKG29	TUBE TOP SINGLE L ENGTH FOLD- PKG29 NOTE TO REMEMBER : *DO NOT USE PINS , CLIPS, STIFFENERS OR CARDBOARD WIT HOUT PRIOR APPRO VAL. FOLDING PREP ARATIONS: *PLACE G ARMENT FACE DOW N. *ALL CLOSURES M UST BUTTON, ZIP, SN AP ETC. FOLDING IN STRUCTIONS: 1. FOL D IN HALF BY BRINGI	00076	KNIT TOPS/TEE SHIR TS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			NG THE BOTTOM OF THE GARMENT TO THE TOP 2. PLACE THE FOLDED GARMENT TINTO THE CORRECT POLYBAG SWITH CLEAR TAPE OR HEAT SEALING HEAT SEALING AUTHOR IS USED ALL POLYBAGS MUST HAVE THREE HALF MOON OR BUTTERFLY VENT HOLES 1/4" DIAMETER AND EVENLY SPACED.)					
	00082	TWISTED BROOMST	TWISTED BROOMST ICK FINISHED DIMEN SIONS AFTER FOLDI NG: FOLDING DIMEN SIONS DEPEND ON LENGTH OF GARMEN T. POLYBAG SHOULD BE ORDERED ACCO RDINGLY TO ASSUR E THAT GARMENT FITS IN BAG TIGHTLY TO HOLD PACKING TE CHNIQUE. IF POLYBAG LENGTH EXCEEDS 23" MUST ANGLE TO FIT INTO STANDARD SIZE CARTON LENGTH DIMENSION 24" *DO NOT FOLD IN HALF * NOTE TO REMEMBE R: *DO NOT USE PIN S, CLIPS, STIFFENER S OR CARDBOARD WITHOUT PRIOR APPROVAL. FOLDING PRE PARATIONS: *PLACE GARMENT FACE UP *ALL CLOSURES MUSTALL CONTROL OF TO STANDED TO CENTER. 2. TWIST VERTICALLY; DO NOT FOLD. 3. SHIP TWIST VERTICALLY; DO NOT FOLD. 3. SHIP TWIST VERTICALLY; DO NOT FOLD. 3. SHIP TWIST USE BING USE BING USE BING USE BING USE BING USE	00143	CRINKLED GARMEN TS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			D, ALL POLYBAGS M UST HAVE THREE HA LF MOON OR BUTTE RFLY VENT HOLES 1/ 4" DIAMETER AND EV ENLY SPACED.					
	01773	UOW BASIC T-SHIRT FOLD (5-14-12)	UOW BASIC T-SHIRT FOLD (5-14-12) FINIS HED DIMENSIONS AF TER FOLDING: FOLDI NG DIMENSIONS DEP END ON LENGTH OF GARMENT. POLYBAG SHOULD BE ORDERE D ACCORDINGLY TO ASSURE THAT GARM ENT FITS IN BAG TIG HTLY TO HOLD PACK ING TECHNIQUE. NO TE TO REMEMBER: * DO NOT USE PINS, C LIPS, STIFFENERS O R CARDBOARD WITH OUT PRIOR APPROV AL. FOLDING PREPA RATIONS: *PLACE GA RMENT FACE UP *AL L CLOSURES MUST Z IP, BUTTON, SNAP E TC. FOLDING INSTRU CTIONS: 1. FOLD HO RIZONTALLY IN- HAL F 2. FOLD VERTICAL LY IN- HALF 3. PACK LOOSELY IN POLYBA G WITH 1/4" EASE AL L AROUND BAG. *IF T HE HEAT SEALING M ETHOD IS BEING USE D, ALL POLYBAGS M UST HAVE THREE HA LF MOON OR BUTTE RFLY VENT HOLES I VENLY SPACED. SEE SEPARATE COMMEN T FOR SIZE STICKER PLACEMENT	00076	KNIT TOPS/TEE SHIR TS	00004	PACKING	

Overview Locat	on Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem	Construction Elem ent Desc	Status
Section 1971	01231	UOW BRAS	UOW BRAS	00176	BRAS	00004	PACKING	
Section 1 and 1 an	01232	UOW PANTY	UOW PANTY	00177	PANTY	00004	PACKING	
	01692	VERTICAL CRINKLE D RESS WITH BODICE SEAM	VERTICAL CRINKLE D RESS WITH BODICE SEAM POLYBAG SHO ULD BE ORDERED A CCORDINGLY TO AS SURE THAT GARMEN T FITS IN BAG TIGHT LY TO HOLD PACKIN G TECHNIQUE. BEND TO FIT INTO CARTON AS SKETCH NOTES T O REMEMBER: *DO N OT USE PINS, CLIPS, STIFFENERS, AND C ARDBOARD WITHOU T PRIOR APPROVAL. FOLDING PREPARAT IONS: *PLACE GARM ENT FACE UP *ALL C LOSURES MUST ZIP, BUTTON, SNAP, ETC . FOLDING INSTRUCT IONS: 1. FOLD BODIC E AT WAIST SEAM 2. GATHER WIDTH OF G ARMENT WITH FINGE RS, COMPRESSING S IDES TOGETHER. 3. P LACE THE FOLDED G ARMENT INTO THE C ORRECT SIZE POLYB AG AND SEAL THE P OLYBAG WITH CLEA R TAPE OR HEAT SE ALING METHOD IS U SED ALL POLYBAGS	00143	CRINKLED GARMEN TS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			MUST HAVE THREE H ALF MOONS OR BUT TERFLY VENT HOLE S 1/4" DIAMETER AN D EVENLY SPACED.					
	01308	VERTICAL ROLL PA CK	VERTICAL ROLL PA CK	00078	WOMEN'S SHIRTS/BL OUSES	00004	PACKING	
	00850	VERTICAL ROLL PAC K-DRESS WITH SLEE VES	VERTICAL ROLL PAC K-DRESS WITH SLEE VES FINISHED DIME NSIONS AFTER FOLD ING/ROLLING: DEPE NDS ON THE LENGT H OF THE GARMENT I POLYBAG SIZE: DO NOT ALLOW MORE T HAN 1" OF SPACE BE TWEEN EDGE OF GA RMENT AND POLYBA G. NOTES TO REMEM BER: "DO NOT USE P INS, CLIPS, STIFFEN ERS OR CARDBOAR D WITHOUT PRIOR A PPROVAL. *TISSUE M AY BE USED ON LIGH TWEIGHT FABRICS (I E. SILKS,RAYON, PO LYESTER ECT.) FOLD ING/ROLLING PREPA RATIONS: *PLACE GA RMENT FACE DOWN *ALL CLOSURES MUS T BUTTON, ZIP, SNAP ECT. FOLDING/ROLLI NG INSTRUCTIONS: 1 FOLD THE LEFT & R IGHT SIDE OF GARM ENT OVER ON THE F OLD LINES/ SEE SKE TCH FOR SLEEVES. 2 ROLL GARMENT FR OM THE BOTTOM TO THE TOP IN A LOOSE ROLL. 3. PLACE ROLL ED GARMENT INTO C ORRECT SIZE POLYB AG AND SEAL THE P OLYBAG WITH CLEA	00075	SHIRTS/DRESSES/JU MPERS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			R TAPE OR HEAT SE AL. (IF THE HEAT SEA LING METHOD IS USE D ALL POLYBAGS MU ST HAVE THREE HAL F MOO OR BUTTERFL Y VENT HOLES 1/4" D IAMETER AND EVENL Y SPACED.)					
	01065	VERTICAL ROLL PAC K-DRESS WITH SLEE VES	VERTICAL ROLL PAC K-DRESS WITH SLEE VES FINISHED DIME NSIONS AFTER FOLD ING/ROLLING: DEPE NDS ON THE LENGT H OF THE GARMENT . POLYBAG SIZE: DO NOT ALLOW MORE T HAN 1" OF SPACE BE TWEEN EDGE OF GA RMENT AND POLYBA G. NOTES TO REMEM BER: "DO NOT USE P INS, CLIPS, STIFFEN ERS OR CARDBOAR D WITHOUT PRIOR A PPROVAL. *TISSUE M AY BE USED ON LIGH TWEIGHT FABRICS (I E. SILKS,RAYON, PO LYESTER ECT.) FOLD ING/ROLLING PREPA RATIONS: "PLACE GA RMENT FACE DOWN "ALL CLOSURES MUS T BUTTON, ZIP, SNAP ECT. FOLDING/ROLLI NG INSTRUCTIONS: 1 . FOLD THE LEFT & IGHT SIDE OF GARM ENT OVER ON THE F OLD LINES/ SEE SKE TCH FOR SLEEVES. 2 . ROLL GARMENT FR OM THE BOTTOM TO THE TOP IN A LOOSE ROLL. 3. PLACE ROLL ED GARMENT INTO C ORRECT SIZE POLYB AG AND SEAL THE P OLYBAG WITH CLEA R TAPE OR HEAT SE AL. (IF THE HEAT SEA LING METHOD IS USE D ALL POLYBAGS MU ST HAVE THREE HAL F MOO OR BUTTERFL		LG SLEEVE KNIT TOP /LGHTWGHT QUILTE D JACKET	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			Y VENT HOLES 1/4" D IAMETER AND EVENL Y SPACED.)					
	01066	VERTICAL ROLL PAC K-DRESS WITH SLEE VES	VERTICAL ROLL PAC K-DRESS WITH SLEE VES FINISHED DIME NSIONS AFTER FOLD ING/ROLLING: DEPE NDS ON THE LENGT H OF THE GARMENT . POLYBAG SIZE: DO NOT ALLOW MORE T HAN 1" OF SPACE BE TWEEN EDGE OF GA RMENT AND POLYBA G. NOTES TO REMEM BER: *DO NOT USE P INS, CLIPS, STIFFEN ERS OR CARDBOAR D WITHOUT PRIOR A PPROVAL. *TISSUE M AY BE USED ON LIGH TWEIGHT FABRICS (I .E. SILKS,RAYON, PO LYESTER ECT.) FOLD ING/ROLLING PREPA RATIONS: *PLACE GA RMENT FACE DOWN *ALL CLOSURES MUS T BUTTON, ZIP, SNAP ECT. FOLDING/ROLLI NG INSTRUCTIONS: 1 . FOLD THE LEFT & R IGHT SIDE OF GARM ENT OVER ON THE F OLD LINES/ SEE SKE TCH FOR SLEEVES. 2 . ROLL GARMENT FR OM THE BOTTOM TO THE TOP IN A LOOSE ROLL. 3. PLACE ROLL ED GARMENT FR OM THE BOTTOM TO THE TOP IN A LOOSE ROLL. 3. PLACE ROLL ED GARMENT FR OM THE BOTTOM TO THE TOP IN A LOOSE ROLL. 3. PLACE ROLL ED GARMENT FR OM THE BOTTOM TO THE TOP IN A LOOSE ROLL. 3. PLACE ROLL ED GARMENT FR OM THE BOTTOM TO THE TOP IN A LOOSE ROLL. 3. PLACE ROLL ED GARMENT FR OM THE BOTTOM TO THE TOP IN A LOOSE ROLL. 3. PLACE ROLL ED GARMENT INTO C ORRECT SIZE POLYB AG AND SEAL THE P OLYBAG WITH CLEA R TAPE OR HEAT SEA LING METHOD IS USE D ALL POLYBAGS MU ST HAVE THREE HAL F MOO OR BUTTERFL Y VENT HOLES 1/4" D IAMETER AND EVENL Y SPACED.)	00076	KNIT TOPS/TEE SHIR TS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
	01067	VERTICAL ROLL PAC K-DRESS WITH SLEE VES	VERTICAL ROLL PAC K-DRESS WITH SLEE VES FINISHED DIME NSIONS AFTER FOLD ING/ROLLING: DEPE NDS ON THE LENGT H OF THE GARMENT . POLYBAG SIZE: DO NOT ALLOW MORE T HAN 1" OF SPACE BE TWEEN EDGE OF GA RMENT AND POLYBA G. NOTES TO REMEM BER: "DO NOT USE P INS, CLIPS, STIFFEN ERS OR CARDBOAR D WITHOUT PRIOR A PPROVAL. "TISSUE M AY BE USED ON LIGH TWEIGHT FABRICS (I .E. SILKS,RAYON, PO LYESTER ECT.) FOLD ING/ROLLING PREPA RATIONS: "PLACE GA RMENT FACE DOWN "ALL CLOSURES MUS T BUTTON, ZIP, SNAP ECT. FOLDING/ROLLI NG INSTRUCTIONS: 1 . FOLD THE LEFT & R IGHT SIDE OF GARM ENT OVER ON THE F OLD LINES/ SEE SKE TCH FOR SLEEVES. 2 . ROLL GARMENT FR OM THE BOTTOM TO THE TOP IN A LOOSE ROLL. 3. PLACE ROLL ED GARMENT INTO C ORRECT SIZE POLYB AG AND SEAL THE P OLYBAG WITH CLEA R TAPE OR HEAT SEA LING METHOD IS USE D ALL POLYBAGS MU ST HAVE THREE HAL F MOO OR BUTTERFL Y VENT HOLES 1/4" D IAMETER AND EVENL Y SPACED.)	00074	ROBES	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem	Construction Elem ent Desc	Status
noll up side to side and put in a poly bag, taper closed	00232	VERTICAL ROLL WIT H TISSUE	VERTICAL ROLL WIT H TISSUE	00071	SKIRTS	00004	PACKING	
	01157	VERTICAL RUMPLE N O TWIST	VERTICAL RUMPLE N O TWIST FINISHED D IMENSIONS AFTER F OLDING: FOLDING D IMENSIONS DEPEND ON LENGTH OF GAR MENT. POLYBAG SH OULD BE ORDERED ACCORDINGLY TO A SSURE THAT GARME NT FITS IN BAG TIGH TLY TO HOLD PACKI NG TECHNIQUE. PAC KED POLY BAG DIME NSIONS MUST NOT E XCEED 23L X 16W NO TES TO REMEMBER: *DO NOT USE PINS, C LIPS, STIFFENERS, A ND CARDBOARD WIT HOUT PRIOR APPRO VAL. FOLDING PREP ARATIONS: *PLACE G ARMENT FACE UP *A LL CLOSURES MUST ZIP, BUTTON, SNAP, ETC. FOLDING INSTR UCTIONS: 1. GATHER WIDTH OF GARMENT WITH FINGERS, COM PRESSING SIDES TO GETHER. 2. PLACE T HE FOLDED GARMEN T INTO THE CORREC T SIZE POLYBAG AN D SEAL THE POLYBA G WITH CLEAR TAPE OR HEAT SEALING M ETHOD IS USED ALL POLYBAGS MUST HA VE THREE HALF MOO NS OR BUTTERFLY V ENT HOLES 1/4" DIAM ETER AND EVENLY S PACED.	00143	CRINKLED GARMEN TS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
	00079	VERTICAL RUMPLE W/ TOP TO BOTTOM CRUSH	VERTICAL RUMPLE W/ TOP TO BOTTOM CRUSH FINISHED DI MENSIONS AFTER F OLDING: FOLDING D IMENSIONS DEPEND ON LENGTH OF GAR MENT. POLYBAG SH OULD BE ORDERED ACCORDINGLY TO A SSURE THAT GARME NT FITS TIGHTLY IN B AG TO HOLD PACKIN G TECHNIQUE. NOTE TO REMEMBER: *DO NOT USE PINS, CLIP S, STIFFENERS OR C ARDBOARD WITHOU T PRIOR APPROVAL. FOLDING PREPARAT IONS: *PLACE GARM ENT FACE UP *ALL C LOSURES MUST ZIP, BUTTON, SNAP ETC. FOLDING INSTRUCTI ONS: 1. GATHER WID TH OF GARMENT WIT H FINGERS, COMPRE SSING SIDES TO CEN TER. 2. PUSH TOP AN D BOTTOM OF GARM ENT TOGETHER. 3. S HIP IN CORRECT SIZ E POLY BAG *IF HEA T SEALING METHOD I S BEING USED, ALL P OLYBAGS MUST HAV E THREE HALF MOO N OR BUTTERFLY VE NT HOLES 1/4" DIAM ETER AND EVENLY S PACED.	00143	CRINKLED GARMEN TS	00004	PACKING	
	00085	VERTICAL RUMPLE WITH LIGHT TWIST	VERTICAL RUMPLE WITH LIGHT TWIST	00143	CRINKLED GARMEN TS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem	Construction Elem ent Desc	Status
	01140	VERTICAL RUMPLE WITH LIGHT TWIST	VERTICAL RUMPLE WITH LIGHT TWIST	00075	SHIRTS/DRESSES/JU MPERS	00004	PACKING	
	01824	VERTICAL RUMPLE WITH LIGHT TWIST - TOP	VERTICAL RUMPLE WITH LIGHT TWIST - TOP	00143	CRINKLED GARMEN TS	00004	PACKING	
	00018	VINTAGE & WESTER N STYLES- PKG17	VINTAGE & WESTER N STYLES- PKG17 FI NISHED DIMENSION S AFTER FOLDING: A PPROXIMATE FOLDE D WIDTH DIMENSION SHOULD BE 10". POL YBAG SIZE: 1/4 - 3/8" EASE BETWEEN BAG SIDES AND GARMEN T EDGES PREFERRE D. NOTES TO REMEM BER: *DO NOT USE P INS, STIFFENERS AN D CARDBOARD WITH OUT PRIOR APPROV AL. FOLDING PREPA ARATIONS: *ALL CLOS URES MUST BUTTON , ZIP, SNAP ETC. *PL ACE GARMENT FACE DOWN FOLDING INST RUCTIONS: 1. FLIP C OLLAR UP. 2. LAY W EARER'S RIGHT COL LAR DOWN FIRST WI TH LEFT COLLAR OV ER TOP. 3. FOLD THE SLEEVE BACK AND D OWN LAYING SLEEV ES FLAT. 4. FOLD UP BOTTOM IN EQUAL T RIPLE FOLD TO ALIG N BOTTOM FOLD WIT H TOP SHOULDER F OLD LINE. 5. PLACE T HE FOLDED GARMEN	00079	MEN'S SHIRTS	00004	PACKING	

Overview Location	Code	Description	Detail	Construction Type	Construction Type Desc	Construction Elem ent	Construction Elem ent Desc	Status
			T INTO CORRECT SIZ E POLY BAG AND SE AL WITH CLEAR TAP E OR HEAT SEAL. (IF HEAT SEALING METH OD IS USED POLY BA GS MUST HAVE 3 HA LF MOON OR BUTTE RFLY VENT HOLES 1/ 4" DIAMETER AND EV ENLY SPACED.)					
FLAT PACKING W/ HANGER	01203	WEDDING GOWN = N O FOLD / FLAT PACK	WEDDING GOWN = N O FOLD / FLAT PACK HANG GARMENT ON HANGER & ENCASE I N POLYBAG. POLYB AG LENGTH MUST = MINIMUM 4" LONGER THAN FINISHED GAR MENT LENGTH. ROL L UP BAG OPENING T O FINISH 1" BELOW G ARMENT HEM AND T APE CLOSED. "TRAIN S EXTENDING BEYO ND CARTON DIMENSI ONS SHOULD HAVE F ULLEST LENGTH BEF ORE SINGLE FOLD A T THE BOTTOM CAR TON SIZE: 67"L X 22" W X 8"D	00212	WEDDING	00004	PACKING	
	01202	WEDDING GOWNS: S INGLE FOLD	WEDDING GOWNS: S INGLE FOLD HANG G ARMENT ON HANGE R & ENCASE IN POLY BAG. POLYBAG LEN GTH MUST = MINIMU M 4" LONGER THAN F INISHED GARMENT L ENGTH. ROLL UP BA G OPENING TO FINIS H 1" BELOW GARMEN T HEM AND TAPE CL OSED. * FOLD AT JOI NT SEAM LIKE BODIC E JOINING OR WAIST AREA *MAXIMUM SIN GLE LENGTH FOLD A S NEEDED TO FIT IN SPECIFIED CONTAIN ER. FLAT PACK IN CA RTON SIZE 50"L X 24 "W X 14"D	00212	WEDDING	00004	PACKING	